



SYMMETRY™ S813 FINGERPRINT CARD READER

The Symmetry S813 reader combines the L-I Identity Solutions® MVI200™ fingerprint sensor with a NXP MIFARE® / MIFARE® DESFire contactless Smart Card chip to produce a high security front end to a Symmetry access control system. The Smart Card is used to store a fingerprint template, so that when the card is presented to the reader, the template is read from the card and the user is prompted to place their finger on the fingerprint sensor. A comparison is then made between the live fingerprint and the stored fingerprint and if the two match, access is permitted.

The Symmetry S813 is able to read NXP MIFARE® and MIFARE® DESFire smart cards. For either type of card, the Symmetry S813 supports the use of unencoded cards (where only the unique card serial number is read), or cards encoded with a card number and optional biometric data. Several encoding formats are supported. The reader is automatically configured to accept the first two card types/formats presented.

The Symmetry S813 has the flexibility to automatically switch between a number of different operating modes.

- Card Only - Operates as a normal contactless Smart Card reader.
- One Finger - The use of only one finger only is required for a match comparison with the template stored in the Smart Card.
- Two Finger - Two factor authentication - Two templates are stored in the Smart Card and the user must present both fingers as prompted by the LCD display for a match comparison.

The Symmetry S813 has a fingerprint acceptance threshold on a per cardholder or per reader basis. A duress capability is also standard. The Symmetry S813 is designed for use with the complete multiNODE range of database and door controllers.

The Symmetry S813 is compatible with Symmetry Business, Symmetry Professional, Symmetry Enterprise and Symmetry Global at Version 4.02 and later; with controller firmware of Version 2.1 or later.

Unlike standard Wiegand interface readers, the Symmetry S813 uses secure, bi-directional, pseudo-random supervised communications between the multiNODE controllers and their associated readers. This advanced protocol provides many benefits such as the ability to turn on and turn off the fingerprint requirement from anywhere on the system using a command at the reader, a special threat level card or from the client software. Also achieved through this integration is the ability to encode and use the threshold directly on the card to increase reliable throughput and security. A distance from any of the multiNODE controllers to the Symmetry S813 reader of up to 3000 feet (1000m) can also be achieved.

The Symmetry S813 includes an LCD for verification of both card and fingerprint read. The LCD is also used for card PIN prompt and for verification of command functions initiated through the reader keypad. The Symmetry S813 has an integrated buzzer for confirmation of card read and local door pre-held warning alarms. This integrated buzzer is also used to give audible feedback for positive confirmation of key press for card PIN entry.



KEY FEATURES

- L-1 Identity Solutions MVI200 fingerprint sensor
- Typical MIFARE/MIFARE DESFire Smart Card read range of 1" (2.5cm)
- Supervised, bi-directional pseudo-random communications
- Integrated door pre-held warning buzzer
- Audible feedback provides positive confirmation of card read and key press
- LCD keypad indicates verification of both card and fingerprint accepted/rejected
- LCD is also used for card PIN prompt and to give verification of command functions initiated through the reader keypad
- Two Fingerprint mode
- Duress mode
- Enrollment integrated in software

SPECIFICATIONS

Model Types

- S813 Fingerprint and Smart Card Reader
- Available in ash gray

Communicating Distances

- multiNODE-1000/multiNODE-2 SMD/multiNODE-2000/multiNODE 2100/ multiNODE 2150 controllers to: Symmetry S813 (current loop) = 3000ft/1000m

Dimensions inches (mm)

- Width = 6.8" (173.2mm)
- Height = 5" (127.5mm)
- Depth = 1.9" (49.13mm) at deepest point

Operating Environment

- 32°F to +122°F (0°C to +50°C)
- 15% to 90% Humidity, non condensing IP605
- For Internal use only

Power Requirements

- Nominal 12VDC (9-14V)
- Maximum current consumption 200mA

APPROVALS

Radio regulatory approvals

- EN 300 330:1999
- FCC Approved

EMC Type Testing

- EN50130-4
- EN 60950:2000
- EN 50357
- EN 50133-1:1997

Access control product testing to

- R & TTE Directive 1999/5/EC

PURCHASING INFORMATION

- 813-KP-AG-001



AMAG Technology

sales@amag.com

www.amag.com