Conway Security Products Limited

EH1,EH3 and EH4 External Camera Housings

The environmental housing is one of the cornerstones of many CCTV installations. Accessibility for camera servicing and long term environmental durability are key points to look for.

The EH1 is designed for large focal length lens applications such as the PentaxTM $12\sim240$ mm model. The size optimises the load centres and therefore reduces wear on pan and tilts.

Manufactured from high quality aluminium alloy all external camera housings models come complete with heater/de-mister.

Camera mounting platforms and cable termination rails are standard plus base stiffener plates. Adapted versions of the stiffener plate can provide a suitable mounting position for the Conway Omega DC telemetry receiver to Delta AC Receiver and Alpha AC Receiver.

Heaters

The heater is used where condensation needs to be prevented or the temperature may fall below a minimum value. PTC heating elements are semiconductors which adjust their performance according to the ambient temperature and are available in either 110-250V AC/DC & 12-36V AC/DC. Please state when ordering required type.

Wipers

The integral wiper option is an innovative design that offers the end-user a neat compact wiper option and overcomes the problem of external wiper units restricting tilt movement.

Special Finishes

At Conway we manufacture all of our products at our own factories in High Wycombe and are therefore able to apply special colour finishes to customer specifications. All-aluminium construction

Integral wiper option

•

12-36v or 110-240v heater

Glass screen

Stainless steel clip fasteners

4" PCD mounting point

Suitable for mounting Conway telemetry receivers

Anti-tamper options

Safety chain between base and lid

Manufactured to weatherproof standard BS.EN60529 Level IP66

Standard Finish BS 10A03 "Morning Mist"

Adjustable horizontal camera mount

Models		
EH1	Camera housing complete with heater/demister	
EH1/w	Camera housing complete with self parking wiper and heater/ demister	
EH3	Camera housing complete with heater/demister	
EH3/w	Camera housing complete with self parking wiper and heater/ demister	Th
EH4	Camera housing complete with heater/demister	TA
EH4/w	Camera housing complete with self parking wiper and heater/ demister	-



EH4/w

Conway Security Products Limited

External Dimensions (mm's)			
	EH1	EH3	EH4
А	584	570	463
В	217	191	160
С	252	207	166.5

Internal Dimensions (mm's)			
	EH1	EH3	EH4
Length	467	467	387
Width	200	174	143
Height	176	131	90

Related Products

WW series washers WW1/5-12, WW1/10-12, WW1/25-12

Pan & Tilts C2020/dc/p, C2020/ac/p, C2090/CR

> Mounting Brackets CMB3, CMB1, CMB0

Stainless Steel Housings EH4/ss, EH3/ss


Using POE?

We have various solutions for customers using POE. Please call our technical department for more details.




Conway Security Products Limited Seymore House, Copyground Lane, High Wycombe, Buckinghamshire HP12 3HE Tel +44 1494 461373 Fax +44 1494 531685 sales@conway-cctv.co.uk www.conway-cctv.co.uk

Datasheet D01-3 March 2009



С





Technical Data			
	EH1	EH3	EH4
Mounting	4" (101.6mm) PCD	4" (101.6mm) PCD	4" (101.6mm) PCD
Window Sizes	172x150mm	146x106mm	115x68.5mm
Glass Sizes	195x174mm	170x130mm	140x96mm
Weight	5.3kg EH1 5.8kg EH1/w	4.2kg EH3 4.7kg EH3/w	2.9kg EH4 3.5kg EH4/w
Paint Finish (powder coat)	BS10A03 ("Morning Mist") base and middle Ral9010 (white) sunvisor	BS10A03 ("Morning Mist") base and middle Ral9010 (white) sunvisor	BS10A03 ("Morning Mist") base and middle Ral9010 (white) sunvisor

Options			
Tl	Anti-tamper screw fitting kit. Prevents lid being removed without tool.		
T2	Anti-tamper microswitch. When lid is removed the microswitch can trigger an alarm when connected to appropriate device.		
/w	Self-parking wiper. Available in 24vac or 220~230vac		

EH PTC Heater Range				
	In Rush Current	In Rush Time	Max Level Off Current	Power Rating
110~230v	140mA	1 Sec Max	26mA	6 Watts
12v	1.7 Amps	1 Sec Max	500mA	6 Watts
24v	1.7 Amps	1 Sec Max	250mA	6 Watts

Pre-Build Service

Conway is able to offer an in-house pre-build service ranging from basic assembly to full design and test solutions. Please contact sales for more information.

Due to a policy of continual improvement, specifications may be subject to change. Drawings not shown to scale.