

960 SPEECH DIGITAL COMMUNICATOR



The 960 is a plug-on auto dialling speech/digital communicator unit, designed to be discreetly fitted in a Scantronic, or certain other manufacturer's alarm control panels.

Should you wish to have your premises monitored by family, friends, neighbours, company members or a remote monitoring centre, the 960 offers a wide variety of choices, tailored to suit your specific budgetary and installation requirements.

The speech communicator option is programmed via a DTMF touch tone telephone and is capable of sending 4 pre-recorded voice messages to family, friends, neighbours, company members etc over the telephone line.

The voice message has one, eight second master message, normally used to record your name and address and up to four, three second secondary messages. These are normally used to indicate the type of incident e.g. personal attack, burglary, fire etc.

The digital communicator option is programmed via a DTMF touch tone telephone using the advanced programming function. This will allow the communicator to be received in Scancom fast format remote monitoring centres.

The Scantronic 960 offers a wide variety of choices should you wish to have your premises monitored, providing enhanced security to your alarm system, giving you total peace of mind.

960

SPEECH DIGITAL COMMUNICATOR

TECHNICAL SPECIFICATION

Plug-on Unit	Designed to be used with any control panel that uses the standard Scantronic plug-on footprint
Number of Communication Channels	8 channel plug-on digital communicator or 4 channel speech communicator
Two Levels of Programming	Programmed as a speech communicator, digital communicator or both. With two levels of programming - basic and advanced
DTMF Programming	Programmed via a DTMF telephone with complete non volatile memory (NVM) backup
Number of Voice Messages	Delivers up to 4 programmed voice messages (one eight second master message, and up to four, three second secondary messages).
Number of Telephone Messages	Calls up to four telephone numbers in sequence, until acknowledged or until 15 attempts are made
Security Code	A security code can be programmed to prevent unauthorized changes to the programmed information
Communicates to a Remote Monitoring Centre	If programmed the 960 will communicate to any alarm receiving equipment that uses Scancom fast format.
Telephone Line Connection	Direct exchange lines (PSTN) supporting DTMF (tone) or loop disconnect (pulse) dialling
Weight	160g
Dimensions (H x W x D)	80 x 170 x 25mm
Power Supply	25mA quiescent
Outputs	Remote or locally controlled. Open collector, 100mA active
Temperature	-10°C to +55°C
Approvals	BABT approved
Scantronic Compatible Equipment	All panels that use Scantronic plug on footprint

Scantronic is a leading brand of Cooper Security Ltd, part of Cooper Industries, employing over 28,000 people in 100 manufacturing sites around the world.

Scantronic manufactures security equipment for all types of commercial and domestic premises. The range is comprehensive, offering every type of solution from multizone hard-wired and wirefree systems, to digital and voice communicators, to detectors and social alarms. Installers trust us to deliver cost effective products with the highest quality of field and support services to ensure you receive the best and most reliable systems to secure you and your premises.

Dealer Details