Granta Security Management System Granta Primo

Model Number	General Desc	Price £ RRP	
4840	Granta Primo Software A simple package providing the basic features of an Access Control System: Cardholders, Access levels, Time Frames, Doors, Inputs, Outputs, Reports, Monitor, Alarms and Administration. Designed for ease of use with all functions presented in a single application window. The software supports both 4101 and 4010 Controllers con- figured within a single RS232 connected Hardware Sys- tem. Fully translated software, help and on-line manu- als. It can be seamlessly upgraded to the Granta Security Management System without change to the connected hardware. Granta Primo is a single PC application (no workstation support) and provides no support for dial-up remote sites, CLIC or other licenced Granta software ap- plications. When combined with the 4010-CPP Controller and Reading Heads provides cost effective two or four door, Hands-Free or Proximity Access Control System		55.00
	Basic PC Requirements	Pentium PIII 500MHz, 128MB RAM, 5 GB hard drive, Windows 2000, NT 4.0 (Win 98), SVGS graphics card with 4MB RAM, 2 serial ports, 1 parallel port & CD ROM	
	System Specifications	Works with 4010 and 4101 modular controllers "Shared RF" provides the most cost effective Hands-Free and Proximity solutions Granta Primo can be upgraded at any time to Granta Security Management System giving access to a range of additional options such as alarm graphics, CCTV manager etc., without hardware redundancy	
	System Capacity	13,000 cardholders using 4010 Controllers, 75,000 cardholders using 4101 Controllers 1,023 access levels 64 time zones 2,048 doors	

Granta Security Management System

Granta Primo Proximity Packs

Model Number	General Description		Price £ RRP
Primo-2-Prox	Two Reading Head Proximity Pack		999.00
	Comprising 4010-CPP Controller (see Note 1), two PR100 Reading Heads and Granta Primo software.		
	Dimensions H x W x D (mm) Environmental Electrical	4010-CPP – 280 x 260 x 140 PR100 - 143 x 40 x 18.5 4010-CPP10 to 40°C, PR10030 to 50°C Integral battery backed 3Amp, 85 to 264Vac PSU, battery not included.	
	Reading Head Capacity	4322 Dual Cotag [®] Reader Module and 814 Reader	
	Card Capacity	Module Cable Assembly 4010-CPP -2,500, expandable to 13,000 using 4105 Memory Expansion Module, 4101 - 13,000, expandable to 75,000 using 4105-2 Memory Expansion Module	
Primo-4-Prox	Four Reading Head Proximity Pack		1,446.00
FFFF	Comprising 4010-CPP Controller (see Note 1), four PR10 Reading Heads, 4322 Dual Cotag® Reader Module and 814 Reader Module Cable Assembly (pre-installed) and Granta Primo software Licence)		
	Dimensions H x W x D (mm) Environmental Electrical Reading Head Capacity	4010-CPP – 280 x 260 x 140 PR100 - 143 x 40 x 18.5 4010-CPP10 to 40°C, PR10030 to 50°C Integral battery backed 3Amp, 85 to 264Vac PSU, battery not included. 4010 CPP – 1Amp, PR100 – 100mA 4	
	Card Capacity	4010-CPP -2,500, expand- able to 13,000 using 4105 Memory Expansion Module, 4101 – 13,000, expand- able to 75,000 using 4105-2 Memory Expansion Module	

Note 1: The 4010-CPP Controller within the Primo Packs does not support remote site connection to Granta software and operates with the communications address 'fixed' at 00. Only one unit may be connected on-line to any Granta system. The system can be expanded by the addition of further 4010-CNP controllers as slaves.

Granta Security Management System

Granta Primo Proximity Packs

General Description		Price £ RRP
Two Reading Head Hands-Free Pack		1,171.00
Comprising 4010-CPP Controller (see Note 1), two Hands- Free HF100 Reading Heads and Granta Primo software		
Dimensions H x W x D (mm) Environmental Electrical	4010-CPP – 280 x 260 x 140 HF100 - 265 x 220 x 29.3 4010-CPP10 to 40°C HF10030 to 50°C Integral battery backed 3Amp, 85 to 264Vac PSU, battery not included 4010 CPP - 1Amp	
Reading Head Capacity Card Capacity	2, expandable to 4 using 4322 Dual Cotag [®] Reader Module and 814 Reader Mod- ule Cable Assembly 4010-CPP -2,500, expand- able to 13,000 using 4105	
	Memory Expansion Module, 4101 - 13,000, expandable to 75,000 using 4105-2 Memory Expansion Module	
Four Reading Head Hands-Free Pack		1,780.00
Comprising 4010-CPP Controller (see Note 1), four Hands-Free HF100 Reading Heads, 4322 Dual Cotag [®] Reader Module and 814 Reader Module Cable Assembly (pre-installed) and Granta Primo software		
Dimensions H x W x D (mm) Environmental Electrical Reading Head Capacity Card Capacity	4010-CPP – 280 x 260 x 140 HF100 - 265 x 220 x 29.3 4010-CPP10 to 40°C HF10030 to 50°C Integral battery backed 3Amp, 85 to 264Vac PSU, battery not included 4010 CPP - 1Amp HF100 – 100mA 4 4010-CPP -2,500, expand- able to 13,000 using 4105 Memory Expansion Module, 4101 - 13,000, expandable to 75,000 using 4105-2 Memory Expansion Module	
	Two Reading Head Han Comprising 4010-CPP C Free HF100 Reading He Dimensions H x W x D (mm) Environmental Electrical Reading Head Capacity Card Capacity Card Capacity Four Reading Head Haa Comprising 4010-CPP C Hands-Free HF100 Read Reader Module and 814 (pre-installed) and Gran Dimensions H x W x D (mm) Environmental Electrical	Two Reading Head Hands-Free PackComprising 4010-CPP Controller (see Note 1), two Hands- Free HF100 Reading Heads and Granta Primo softwareDimensions4010-CPP - 280 x 260 x 140H x W x D (mm)HF100 - 265 x 220 x 29.3Environmental4010-CPP - 10 to 40°CHF100 - 30 to 50°CIntegral battery backed 3Amp, 85 to 264Vac PSU, battery not includedReading Head Capacity2, expandable to 4 using 4322 Dual Cotag® Reader Module and 814 Reader Mod- ule Cable AssemblyCard Capacity4010-CPP -2,500, expand- able to 13,000 using 4105 Memory Expansion Module, 4101 - 13,000, expandable to 75,000 using 4105-2 Memory Expansion ModuleFour Reading Head Hands-Free PackComprising 4010-CPP Controller (see Note 1), four Hands-Free HF100 Reading Heads, 4322 Dual Cotag® Reader Module and 814 Reader Module Cable Assembly (pre-installed) and Granta Primo softwareDimensions4010-CPP – 280 x 260 x 140 H X W x D (mm)H × W x D (mm)HF100 - 265 x 220 x 29.3Environmental4010-CPP – -10 to 40°C HF100 - 30 to 50°CElectricalIntegral battery backed 3Amp, 85 to 264Vac PSU, battery not included 4010 CPP - 10 to 40°C HF100 - 100mAReading Head Capacity4Acid Capacity4Acid Capacity4Acid Capacity4Cord Capacity4Acid Capacity4Acid Capacity4Acid Capacity4Acid Capacity4Acid Capacity4Acid Capacity4Acid Capacity4Acid Capacity

Note 1: The 4010-CPP Controller within the Primo Packs does not support remote site connection to Granta software and operates with the communications address 'fixed' at 00. Only one unit may be connected on-line to any Granta system. The system can be expanded by the addition of further 4010-CNP controllers as slaves