



EDC-KBD1

Article-No.: 74088

System Keyboard with 3-axis
Joystick, 12VDC

Mainfeatures

Programming and control of camera series:
For DVR series DLR1.2, DLR3/4, DTR, DIR and DPR
Joystick control of PTZ functions
Preset position and pattern control

Fastrax and Minitrax
Supports up to 254 cameras
Programmable sequences and patterns
Auto and random scanning

Specifications

Integrated monitor	-
Video input	-
Site control (direct mode operation)	Keys select cameras and monitors, operates up to 254 presets, 4 patterns, 8 scans. Capability to incorporate up to 300 of presets, patterns, scan and tour itself in up to 8 tours. Camera functions: pan, tilt, zoom, focus, iris for fixed or variable speed control of the camera series Fastrax, Minitrax. Auxiliaries and sequences.
Baud rate	2.400 ~ 230.000
Interface	3x RS-485, RJ45 (8-pin). 1x KBD (For connection of the junction box: Dome camera series Fastrax), 1x DVR (Recorder series DLR, DTR, DPR)
Remote control	Control of up to 254 Fastrax and/or Minitrax dome cameras, camera series Almira. Up to 99 Digital Video recorders of the series DLR and DTR
LCD display	16x2 characters
Supply voltage	12VDC (connection to the Junction box, 230VAC PSU included)
Power consumption	Approx. 5 watts

Specifications (continued)

Temperature range	0 ~ +50°C
Dimensions (HxWxD)	96 (incl. Joystick) x380x168mm
Weight	approx. 1.2kg
Parts supplied	System keyboard, Junction box with connection cable and PSU
Certificates	CE

Your partner for eneo products:

