



## BM3

Access Control

## Door entry phone for PABX

- 
- **Analog extension for the PABX system**
  - **Includes button for hotline function, CCTV control and tamper switch**

BM3 is used as an analog extension for the PABX internal tele phone system. It incorporates a built-in codelock with four codes. The BM3 also includes CCTV control and a tamper switch.

Connected telephone sets must be able to generate a standard tone signal (DTMF).

## Technical data

---

| <b>BM3</b>             |   |
|------------------------|---|
| Interface              | Two analog extension cables for PABX  |
| Housing                | Cast metal with stainless steel buttons and security lock. For flush mounting, use BB5 flush mounting kit.                |
| Environment            | Indoor or outdoor use. In very exposed locations, use SH3 or SH1 rain cover.  |
| IP rating              | IP54  |
| Operating temperature  | -35 to +50 °C. At 90% relative air humidity.  |
| Operating voltage      | 12 to 24 VAC/DC   |
| Current consumption    | 60 mA in standby  |
| Dimensions (W x H x D) | 80 x 200 x 40 mm  |
| Calling time           | 1-99 seconds (can be extended x10)  |
| Code capacity          | 4   |
| Inputs                 | Exit button request with delay. Two inputs for disabling respective codes.  |
| Outputs                | Voltage-free relay contact, max. 2 A 28 VDC. Tamper switch for alarm (normally closed). Relay for control of CCTV system. |
| Opening time           | 1-99 seconds programmable from keypad (can be extended x10).  |

## Details for ordering

---

| Type | Part no         | Designation               | Weight |
|------|-----------------|---------------------------|--------|
| BM3  | S24246-C7900-A1 | Door entry phone for PABX | 1.2 kg |

Issued by  
Bewator AB  
SE-171 24 Solna  
Sweden

[www.sbt.siemens.com](http://www.sbt.siemens.com)

© 2008 Copyright by  
Bewator AB, a Siemens company  
Data and design subject to change without notice.  
Supply subject to availability.

---

Document no. **A6V10081708**  
Edition 04.2008