

	MX-D14DI-IT	MX-D14DI-SEC	MX-D14DI-SEC-180	MX-D14DI-SEC-NIGHT-180
D14D Hardware Features				
Outdoor – weatherproof	IP54/IP65 ¹	IP54/IP65 ¹	IP54/IP65 ¹	IP54/IP65 ¹
Ethernet/Mini USB/MxBus/MicroSD	X	X	X	X
MicroSD slot (internal DVR, max. 64 GB)	X	X	X	X
Image sensors	2x color, color/BW, 2x BW	2x color	2x BW	2x BW
Lenses	L22, L32, L43, L65, L135	L22/L22	L22/L22	L22/L22
Resolution (per sensor)	VGA	3/1MEGA ²	3MEGA ²	1MEGA ²
Resolution horizontal x vertical (per sensor)	640 x 480	2048 x 1536, 1280 x 960	2048 x 1536	1280 x 960
Max. frame rate (fps) CIF/VGA/MEGA/3MEGA	30/30/–/–	30/30/30/20	30/30/30/20	30/30/30/–
Sensitivity of color sensor at 1/60 second (lux)	1	1	1	–
Sensitivity of BW sensor at 1/60 second (lux)	0.1	0.1	0.1	0.1
Sensitivity of color sensor at 1 second (lux)	0.05	0.05	0.05	–
Sensitivity of BW sensor at 1 second (lux)	0.005	0.005	0.005	0.005
Automatic night mode switch for color/BW	X	X	–	–
RAM storage (MB)	64	128	128	128
Temp. video storage (MB), ring buffer	32	64	64	64
Internal DVR (MicroSD) ³ , ring buffer:	up to 64 GB	up to 64 GB	up to 64 GB	up to 64 GB
• CIF images (64 GB int. DVR), approx.	4 million ⁴	4 million ⁴	2 million	2 million
• VGA images (64 GB int. DVR), approx.	2 million ⁴	2 million ⁴	1 million	1 million
• MEGA images (64 GB int. DVR), approx.	–	700,000 ⁴	350,000	350,000
• 3MEGA images (64 GB int. DVR), approx.	–	320,000 ⁴	160,000	–
Speaker and microphone	X	X	X	X
Warranty (months)	24	24	24	24
Concealed cabling	X	X	X	X
Special D14D Software Features				
Dual image display	X	X	X	X
Dual image storage	X	X	X	X
Dual image adjustment for 180°	–	–	X	X
Special exposure mode for 180°	–	–	X	X

¹IP65 only with
Outdoor Wall Mount

²Color sensor: 3MEGA
resolution with
2048 x 1536 pixels;
BW sensor: 1MEGA
resolution with
1280 x 960 pixels

³4-GB MicroSD card
pre-installed

⁴Estimated number
of images in single
image mode; in the
case of dual images
(right and left lens),
the number of images
is halved accordingly