



### Specification

Signal system	NTSC		PAL	
Image system				
Imaging area	4.9mm x 3.7mm			
Image pickup device	1/3"-type super HAD CCD			
Effective pixels(HxV)	768 x 494		752 x 582	
Electric				
Scanning system	2:1 Interlace V: 59.94Hz,		2:1 Interlace V: 50Hz,	
	H: 15.734KHz		H: 15.625KHz	
Sync system	Internal / linelock			
Horizontal resolution	540 TV lines			
Lens mount	CS with easy backfocus			
Gamma correction	0.45/1			
Minimum illumination	0.03lux(F1.2, AGC on, 10 IRE); 0.55lux(F1.2, AGC on, 50 IRE)			
S/N ratio	More than 50dB (AGC off)			
Iris control	Video / DC driver			
Gain control	Turbo/Normal/OFF			
White balance	ATW1/ATW2/Manual			
Electric shutter	Auto / 9 steps From 1/60 to 1/100,000sec.		Auto/ 9 steps from 1/50 to 1/100,000sec.	
BLC	BLC1/BLC2/BLC3/BLC4/BLC5/BLC6/Off			
Day/Night mode	Yes(Easy day-night)			
DNR	Yes			
OSD	Yes			
Privacy zone	8 privacy zones			
Remote control	Yes			
Video output	1Vpp composite output 75 ohm, Y/C output			
Power supply				
Power requirement	DC12V / AC24V		AC90~260V DC12V / AC24V	
Power consumption	6.0W (max.)			
Environment				
Operating temperature	-10°C ~ 50°C			
Operating humidity	30% ~ 90% RH			
Storage temperature	-20°C ~ 60°C			
Mechanism				
Dimensions(WxHxD)	50mm x 62mm x 126mm			
	(1.96" x 2.44" x 4.96")			
Weight	500g approx.			
Ordering information	SCB250PRO-HN5		SCB250PRO-HP7	SCB250PRO-HP5

2008.06.06