



Specification

| Signal system | NTSC | | PAL | |
|-----------------------|--|--|--|---------------|
| Image system | | | | |
| Imaging area | 4.9mm x 3.7mm | | | |
| Image pickup device | 1/3"-type super HAD CCD | | | |
| Effective pixels(HxV) | 768 x 494 | | 752 x 582 | |
| Electric | | | | |
| Scanning system | 2:1 Interlace V: 59.94Hz, | | 2:1 Interlace V: 50Hz, | |
| | H: 15.734KHz | | H: 15.625KHz | |
| Sync system | Internal / linelock | | | |
| Horizontal resolution | 480/500TV lines | | | |
| Lens mount | CS | | | |
| Gamma correction | 0.45 | | | |
| Minimum illumination | Day mode: 0.03 lux(F1.4, AGC on, 10 IRE) | | | |
| | Night mode: 0.008 lux(F1.4, AGC on, 10 IRE) | | | |
| S/N ratio | More than 50dB (AGC off) | | | |
| Iris control | Video / DC driver | | | |
| Gain control | Auto(standard / wide) | | | |
| White balance | ATW1 / ATW2 | | | |
| Electric shutter | Auto 1/60 to 1/100,000sec. / manual 8 steps (1/60, 1/100, 1/250, 1/500, 1/1K, 1/2K, 1/4K, 1/10Ksec.) | | Auto 1/50 to 1/100,000sec. / manual 8 steps (1/50, 1/120, 1/250, 1/500, 1/1K, 1/2K, 1/4K, 1/10Ksec.) | |
| BLC | On / off | | | |
| Day/Night mode | Auto / manual | | | |
| OSD | - | | | |
| Remote control | - | | | |
| Video output | 1Vpp composite output, 75 ohm | | | |
| Power supply | | | | |
| Power requirement | DC12V / AC24V | | AC90~260V | DC12V / AC24V |
| Power consumption | 10W (max.) | | | |
| Environment | | | | |
| Operating temperature | -10°C ~ 50°C | | | |
| Operating humidity | 30% ~ 90% RH | | | |
| Storage temperature | -20°C ~ 60°C | | | |
| Mechanism | | | | |
| Dimensions(WxHxD) | 50mm x 62mm x 126mm | | | |
| | (1.96" x 2.44" x 4.96") | | | |
| Weight | 500g approx. | | | |
| Ordering information | SCB260-HN5 | | SCB260-HP7 | SCB260-HP5 |