

Video Security



VK-134

1/3" B/W Board Camera in Housing
with 3.6mm Lens, 12VDC, 380TVL

Art-No. 91747



Features

CCD B&W Board Camera with Housing
1/3" CCD Sensor
Resolution of 420 Horizontal Lines
Electronic Shutter Control (ESC)
Internal Synchronization

High Sensitivity
Interchangeable Lens Element
Supply Voltage: 12 VDC
Micro Compact Version

Specifications

System	CCIR
Imager	1/3" Sony Super HAD Interline Transfer CCD
Active picture elements	Approx. 290,000 (H) 500 x (V) 582
Synchronization	Internal
Gamma correction	0.45
Horizontal resolution	420 TV lines
Sensitivity at 50% video signal	1.6Lux at F2.0 / 0.58Lux at F1.2 (VT measurement result)
Electronic shutter control (ESC)	1/50 to 1/100,000 sec.
Aperture Correction (APC)	Yes
Integrated lens	F 2.0/3.6 mm
Horizontal angle of view	69°
External connections	Video (BNC), 12 VDC (DC socket)
Video output	1 Vp-p, VBS, 75 ohms
Supply voltage	12 VDC (+/-10%)
Power consumption	1.2watts
Temperature range	-10°C to +50°C
Dimensions (HxWxD)	32x32x28 mm
Weight	48 g

Accessories

40059 / H0225M	F2.5/2.5mm Board Camera Lens, 1/3" M12X0.5
40061 / H0820M	F2.0/8mm Board Camera Lens, 1/3" M12X0.5
77779 / VT-PS12DC-UK	Power Supply Unit w. UK Mains plug-in, 100-240VAC/12VDC-1.0A, Regul., open Ends
40065 / H1225	F2.5/12mm Board camera lens, 1/3" M12x0.5
40072 / H0620M	F2.0/6mm Board Camera Lens, 1/3" M12x0.5
70447 / VT-PS12DC-5	Plug-in Power Supply Unit 100-240VAC 12VDC (1.0Amp), Regulated, with DC Plug