

# AV3135 3/1.3 Megapixel Dual Sensor Day/Night Camera

## *Bid-Spec* \_\_\_\_\_

### **1.0 Description**

The AV3135 camera is dual encoder (H.264 & MJPEG), 3/1.3 Megapixel resolution, dual sensor, IP addressable day/night camera, designed to deliver full motion high definition progressive scan digital video across local area networks. The AV3135 has a high sensitivity and is PoE (IEEE 802.3af) compliant. Built with Arecont Vision's proprietary massively-parallel MegaVideo® technology, the AV3135 has the ability to output multiple image formats allowing the simultaneous viewing of the full resolution field of view and regions of interest for high definition forensic zooming. This camera offers over ten times the resolution of standard resolution IP cameras with the ability to output full real time frame rates.

### **2.0 Bid Specification**

- The camera shall be a dual sensor camera.
- The camera shall utilize a high sensitivity 3 Megapixel CMOS color sensor and a 1.3 Megapixel CMOS B/W sensor each with 1/2" optical format.
- The camera shall support two lenses, one for each imager. Each lens to have a maximum diameter of less than 1.5 inches.
- The camera shall be H.264 (MPEG4, Part 10) compliant
- The camera shall have dual standard compression support with simultaneous streaming of both H.264 and MJPEG formats.
- The camera shall have multi-streaming support of up to 8 non-identical concurrent streams (different frame rate, bit rate, resolution, quality, and compression format).
- The camera shall have bit rate control for full view, multi view, and archiving
- The camera's bit rate control shall be selectable from 100 Kbps to 10 Mbps for each independent stream.
- The camera shall have Real Time Streaming Protocol (RTSP) support allowing for compatibility with media players such as Windows Media Player, Apple QuickTime, VLC Player and others.
- The camera's H.264 implementation shall maintain full real time video frame rates.
- The camera shall output at a maximum resolution of 2048(H) x 1536(V) pixels at a maximum frame rate of 15 frames per second (FPS) in color mode.
- The camera shall output at a maximum resolution of 1280(H) x 1024(V) pixels at a maximum frame rate of 15 frames per second (FPS) in black and white mode.
- It shall be possible to program the camera to output a variety of lower resolution images. For example 1280(H) x 1024(V) pixels at 32 FPS, or 1600(H) x 1200(V) pixels at 24 FPS.
- The camera shall feature streaming of the full field of view (FOV) and multiple regions of interest (ROI) for forensic zooming.
- The camera shall be equipped with a 100 Mbps LAN connector and can deliver image data at a maximum data rate of up to 55 Megabits per second (55 Mbps).
- The camera shall use a wide variety of C/CS mount 1/2" lenses. (Note that some CS lenses and all C-mount lenses may require an adaptor ring. Megapixel quality lenses are the preferred choice for our entire camera line.)
- The camera shall provide 21 levels of compression quality for optimal viewing and archiving.
- The camera shall support a minimum TFTP, HTTP, RTSP, RTP/TCP and RTP/UDP network protocols.
- The camera shall feature precision motion detection with a minimum of 64 detection zones
- The camera shall feature automatic exposure, automatic multi-matrix white balance, shutter speed control, 50/60Hz selectable flicker control, programmable brightness, saturation, gamma, sharpness, windowing and decimation, simultaneous delivery of full-field view and zoomed

images at video frame rate, instantaneous electronic zoom, pan and tilt, and electronic image rotation by 180 degrees.

- The camera shall incorporate necessary algorithms and circuits to detect motion in low light with clarity.
- The camera shall support a minimum illumination of 0.2 Lux @ F1.4 in color mode.
- The camera shall support an IR sensitive minimum illumination of 0 Lux in B/W mode
- The camera's primary power source shall be Power over Ethernet (PoE) complying with the IEEE 802.3af standard.
- The camera shall have the alternative option to be powered from between a 12V DC up to 48V DC or 24V AC power source providing at least 5 Watts of power.
- This camera shall feature a durable aluminum housing that minimizes fire hazards. Camera should be mounted using a 1/4" x 20 threaded hole at the bottom or top of the housing.
- The camera shall be utilized for indoor use but can be used in outdoor applications with an appropriate enclosure.
- The camera's operating ambient temperature is 0°C (32°F) to 50°C (122°F).
- The camera shall be FCC Part 15, Class B, CE and RoHS compliant
- The camera shall have dimensions of: 3" (76mm) W x 2.5" (63.5mm) H x 2.25" (57mm) D weighing 8.6oz (243g) without lenses.

---

## Quick-Spec

### 3.0 Minimum Performance Specification

Megapixel camera must meet the following operating requirements

#### Operational

Imaging	3 megapixel color CMOS image sensor 1.3 megapixel b&W CMOS image sensor 1/2" optical format Bayer mosaic RGB filter for color sensor
Active Pixel Count	Color sensor: 2048(H) x 1536(V) pixel array B/W sensor: 1280(H) x 1024(V) pixel array
Minimum illumination	Color: 0.2 Lux @ F1.4 DayNight: 0 Lux, IR sensitive
Dynamic range	61 dB
Maximum SNR	49 dB

#### Full Field of View (FOV) Resolutions

2048x1536 (HxW) 3 megapixel  
1024x768 (HxW) 1/4 resolution  
1280x1024 (HxW) 1.3 megapixel  
640x512 (HxW) 1/4 resolution

#### Cropped Field of View Resolutions

1920x1200 WUXGA  
1920x1080 HDTV-1080p  
1600x1200 2 MP  
1280x1024 1.3 MP  
1280x720 HDTV - 720p  
1024x768 XGA  
800x600 SVGA  
704x570 PAL  
704x480 NTSC  
640x480 VGA  
352x288 CIF

**Data Transmission**

Video frame rate up to:

- 15fps @ 2048x1536
- 20fps @ 1920x1200
- 22fps @ 1920x1080
- 24fps @ 1600x1200
- 32fps @ 1280x1024

Compression type

- H.264 (MPEG4, Part 10)
- Motion JPEG
- 21 levels of quality

TFTP, HTTP, RTSP, RTP/TCP, RTP/UDP image transmission protocols

100Base-T Ethernet Network Interface

Data rate

- bit rate control available for full view, multi view, and archive
- bit rate control from 100 Kbps to 10 Mbps
- unthrottled data rate up to 55 Mbps

Multi-streaming: 8 non-identical streams

**Programmability**

Auto Exposure (AE) and Gain Control (AGC) >120dB

On-camera real-time motion detection with 64 detection zones

Auto backlight compensation

Auto multi-matrix white balance

50/60Hz selectable flicker control

Electronic pan, tilt, zoom (PTZ)

Electronic image flip - 180 degree rotation

Resolution windowing down to 32x32 pixels window

Programmable shutter speeds to minimize motion blur

MoonLight™ mode - extended exposure and proprietary noise cancellation

Programmable resolution, brightness, saturation, gamma, sharpness, tint

Picture-in-Picture: simultaneous delivery of full field of view and zoomed images

Bandwidth & storage savings by running at 1/4 resolution

**Electrical**

General purpose opto-coupled input and output

Power over Ethernet (PoE): PoE 802.3af

DC input: auxiliary 12 V – 48 V DC

AC input: auxiliary 24 V AC

Power consumption 5 Watts maximum

**Mechanical**

Dimensions(H x W x D).....3"W (76 mm) x 2.5"H (63.5 mm) x 2.25"D (57mm) (w/o lens)

Weight.....8.6 oz (243 grams) (w/o lens)

Lens.....C/CS lens mount

**Environmental**

Operating temperature 0°C (32 °F) to +50°C (122 °F)

Storage temperature -20°C (-4 °F) to +60°C (140 °F)

Humidity 0% to 90% (non condensing)

**Regulatory**

- FCC, Class B
- CE and RoHS compliant

**Related Documentation**

1. AV User Manual
2. AV Software Developer Kit Manual
3. AV1305, AV2105, AV3105, AV3135, AV5105 Network Camera Specification

**4.0 Model Numbers**

The camera shall be Arecont Vision model AV3135, dual sensor 3/1.3 megapixel day night camera

**5.0 Warranty**

Minimum 1 Year parts and labor

*Arecont Vision reserves the right to change products or specifications without notice.*