

1/3" Mini Vandal Resistant Fixed Dome
Camera



FEATURES

- 520 TV Lines Horizontal Resolution
- Digital Noise Reduction
- 3 Way Axis Gimbal, wall mountable
- Power Input DC12V

SPECIFICATIONS

Image Sensor	1/3" CCD (Sony Super HAD)
Scanning System	PAL, 50Hz, 2:1 Inter Line Transfer
Pixels - Effective	752 x 582
Resolution	520 (H) lines
S/N Ratio	50 dB
Sensitivity	0.5 lux
AGC	+18 dB max.
Sens Up	x8, auto
Gamma correction	0.45 or 1.0 (by software)
White Balance	ATW
DNR	On/Off
Lens Focal Length	3.8 mm
Lens Drive Type	DC auto iris
Viewing Angle	71°(H) ~ 53°(V)
Video Output(s)	1 CH Composite, BNC female, 1 Vpp
Case colour	Silver
IP Class	65
Operating Temperature	-10°C ~ +50°C
Humidity	less than 90%
Supply Voltage	12 VDC +10%, -5%
Power Consumption	1 W
Weight	0.26 kg
Dimensions w*h*d	Ø 80 x 60.5 mm

Design and specifications are subject to change without notice

Status 03/2008