

16 ch Colour Real-Time Multiplexer



## FEATURES

- 16 channel real time display
- Full triplex operation simultaneous playback and recording and simultaneous display of playback and live pictures on the same screen
- Automatic synchronisation for time-lapse recorder
- 19" rack adapter and external power supply included

## SPECIFICATIONS

Video Input(s)	16 CH Composite, BNC, Looped, 1 VCR, 1 S-VHS
Video Output(s)	1 VCR (BNC), 1 S-VHS, 1 main monitor, 1 call monitor
Display Speed	400 fps
Display Mode	Full screen, 2x2, 3x3, 4x4, 12+1, PIP, Zoom
Recording Speed	50 fps
Video Loss Detection	16 channels
Video Freeze	yes
Alarm Input(s)	16
Alarm Output(s)	1 Relay
Motion Detection	On/Off/Area Setting
OSD	10 characters title generator for each camera, time on screen, setup
Multiplex Function	Triplex
Auto Switching	Programmable sequenzial switch and adjustable dwelling time (2-255 sec)
Security	Security lock
Serial Interface(s)	Supports RS-232 (e.g. barcodes, intercom, POS-systems), RS422 ptz/dome control
Supply Voltage	12 VDC +10%, -5%
Power Consumption	18 W
Weight	5 kg
Dimensions w*h*d	438 x 44 x 310 mm

Design and specifications are subject to change without notice

Status 03/2008