

1/3" CCD C/B&W 1.3 MP IP Anti
Vandal Fixed Dome



FEATURES

- 1.3 Megapixels, Colour/B&W Camera (1280 x 960)
- High Image Quality 1280 x 960
- 3 Way Axis Gimbal, wall mountable
- Varifocal Lens: f = 3.3 - 12 mm, auto iris
- Day/Night feature with removable IR cut filter
- MPEG4 compression modes (max. 25 fps)
- SD memory card slot for alarm image recording
- Video motion detection and pre/post-alarm buffer
- Easy Network Setup such as TCP/IP, HTTP, DHCP, DNS, RTP/PTCP, PPOE
- Bidirectional Audio Support
- Compatible RTP/RTSP
- Power Input AC24V/DC12V and PoE
- Web Viewer by Internet Explorer or by Software included

SPECIFICATIONS

Image Sensor	1.3 Megapixel CCD
Pixels - total	1280 (H) x 960 (V)
Sensitivity Colour	0.1 lux
Col/B&W	On/Off/Auto, removable IR-cut filtre
Motion Detection	On/Off/Sensitivity
BLC	On/Off
AGC	On (Auto)
ELC	On/Off
Camera ID	203 character
White Balance	ATW
Lens Drive Type	DC auto iris
Lens Focal Length	3.3 ~ 12 mm
Alarm Inputs	1
Alarm Outputs	1 Relay

Design and specifications are subject to change without notice

Status 09/2009

1/3" CCD C/B&W 1.3 MP IP Anti
Vandal Fixed Dome

SPECIFICATIONS

Remote Control	RS-485, addressable, multiprotocoll
Operating System	Embedded Linux
Client OS	Win 2000 / XP / VISTA
Web Browser	MS Internet Explorer 5.0 (or higher)
Video Compression	MPEG4 dual compression stream
Audio Compression	OggVorbis 16Kbps
Network Streaming	TCP, UDP (Unicast, Multicast)
Network Protocol	TCP, UDP, RTP, Multicast, HTTP, DHCP, PPPoE, etc.
Video Resolution	1280 X 720 (25 fps), 704 x 576 (25 fps)
Frame Rate	25/22/20/18/16/15/12/10/8/6/4/2/1/0.5/0.25/0.12/0.06 fps
Alarm Event	Alarm Input, Motion Detection or Schedule: Image transfer FTP
IP Installer	IP Address Installation Function (Win XP, VISTA & 2000 support)
Firmware Upgrade	Firmware upgrade by Web Browser
Login Access Level	The administrator can create up to 15 separate users with different right levels
Time Setting	Setting by Software local or internet
Recording	MPEG4
HTTP API	Provides functionality to control cameras and set/retrieve internal parameter values.
Windows API	ActiveX components for viewing streams from video camera.
Input/Output sockets	Power(jack), RJ-45, SD Card Slot, Terminal 6Pin(Alarm In 2Pin, Alarm Out 2Pin, RS485 2Pin)
Operating Temperature	-10°C ~ +60°C
Humidity	less than 90%
Protection Rating	IP66
LED Indicator	Yes
Supply Voltage	12 VDC / 24 VAC / PoE
Power Consumption	4 W
Weight	1.4 kg
Dimensions w*h*d	Ø 156 x 134.5 mm