NULTIMEDIA READY

AG Neovo M-Series Displays

Made for those who want enhanced multimedia power



Elegant & Rugged Design

Smart exterior with exceptional strength



Brilliant Display

Patent pending NeoV Crystal Optic Filter offers superb color definition and image sharpness



Ease Of Use

A host of input options, including analog, S-video and USB



Multimedia Power

Built-in amplifier and speakers for an enhanced audio-visual experience



Customer Satisfaction

Global after-sales service, and a 3 year limited warranty



Features

Neo-V Crystal Optic Filter 15" TFT Active Matrix Screen 1024x768 Resolution Built-In Amplifier and Speakers Analog, Video & USB Inputs






NeoV Crystal Optic Filter

Triple coated on both sides, the NeoV Crystal Optic Filter offers anti-glare, anti-reflective properties, while delivering greater color defi-

Wide angle viewing technology offers greater viewing clarity even when the display is seen from different angles.



video in port. **Built-in Speakers**

Eliminate the need for external speakers, and enjoy a rich multimedia experience.



360 Degree Swivel

Built-in 360 degree swivel base ensures obtaining the optimal viewing angle.



USB Connector

Four powered USB ports maximize the connectivity of all USB peripherals.



Total Flat Display

A completely flat display, with absolutely no curvature, generates a truer and less distorted



Auto-Adjustment

Automatically adjusts screen settings for an optimal image, without changing settings manually.



LCD Panel Protection

Protects the LCD panel from potential damage caused by repeated touching of the surface.



On-Screen Display (OSD) makes adjusting the display settings quick and convenient.





Specifications

Inputs

Connector

Crystal Optic Filter

Dimensions

NeoV

Panel

Panel Type Panel Size Max. Resolution Pixel Pitch **Brightness** Contrast Ratio **Surface Treatments**

Viewing Angle (H/V) Display Color Response Time MVA® Technology Frequency

Max. Pixel Clock

USB Analog Video

Speaker

Power

Thickness Reflection Rate Transmission Rate Hardness (Moh's Rating)

Tilt/Swivel Tilt Angle / Swivel Mounting **VESA FPMPMI**

Packing (W x H x D)

Net Weight Gross Weight

Net (W x H x D)

Regulation

Power

Approval

Weight

Safety & EMI

VESA

Power AC Consumption 100~240V, 50~60Hz < 48W (On)

M-15V

TFT LCD

0.297mm 250cd/m² (Typical)

16 7M

80MHz

15.0" (381mm) XGA 1024 x 768

400:1 (Typical)

Hard Coating (2H)

& Anti-glare treatment 160°/160° (Minimum)

15ms /10ms (Typical)

Yes (1 Up/4 Down)

15-Pin Mini D-Sub 4-Pin Mini Din S-Video

RCA Jack CVBS

3-Pin AC Plug

2.8mm (0.11")

3°~ 90°/ Swivel

391 x 396 x 180mm

(15.4" x 15.6" x 7.1")

475 x 480 x 210mm

(18.7" x 18.9" x 8.3")

FCC, UL/CUL, EPA, TUV/GS, CE, NORDIC, TCO95, NUTEK,

7.0Kg (15.4lb)

9.0Kg (19.8lb)

BSMI, VCCI, CB

DDC1/2B, DPMS

< 1% > 94%

> 6H

N/A

Yes (1.5W)

Horizontal: 30kHz - 60kHz Vertical: 50Hz - 75Hz

< 5W (Stand-by) < 5W (Off)

All specifications are subject to change without prior notice. © 2002 Associated Industries China Inc. The name AG Neovo is a trademark of AIC. All other trademarks are the property of their respective owners.

Optional Accessories





















A Different Class Of Display

Asia Associated Industries China, Inc. 10F, No.15, Chi-Nan Road, Sec. 1 Taipei, Taiwan R.O.C. Tel +886-2-2357-5896 Fax +886-2-3393-2475 marketing@neovo.com www.neovo.com

North America AG Neovo Technology Corp. 2380 Qume Drive, Suite C

San Jose, CA 95131, USA Tel +1-408-321-8210 Fax +1-408-321-8211 info@neovo-usa.com www.neovo-usa.com

AG Neovo Technology B.V. Eglantierbaan 8 2908 LV Capelle A/D ljssel The Netherlands Tel +31-10-442-57-37 Fax +31-10-442-57-42 service@agneovo.nl www.agneovo.nl

Online

Visit www.neovo.com for the latest information on AG Neovo's range of award winning displays.

Dealers Stamp:

DM Code: MKT-M5E-0102