

## TX-15



LED 

The text 'LED' is followed by a small icon consisting of four colored dots (red, green, blue, yellow) arranged in a square.

A 15" 10-point touch display with front-sided IP65 designed specifically for professional interactive applications.

The TX-15 is a 10-point touch display with a compact size for environments where space is at a premium. State-of-the-art projected capacitive technology enables users to experience smooth and precise on-screen navigation. With a glass overlay, the TX-15 brings considerable benefits such as ease-to-clean and product durability. Coming with front-sided IP65 rating, the TX-15 is effectively protected against the ingress of liquid and dust. Built on durable metal housing and rugged base design, the TX-15 is suitable for the most demanding public and industrial environments.

- > Incorporates advanced projected capacitive touch technology
- > 10-point touch capabilities for systems with Microsoft® Windows® 7 and 8
- > Supports Microsoft® Windows® 7, 8, XP, Vista, 2000, Mac OS X, Linux
- > LED-backlit technology with 1024 x 768 resolution
- > Flush touch screen makes surface neat and clean
- > Front-sided IP65 rating protects screen from liquid and dust
- > Whole enclosure designed with IPX1 level for drip-proof
- > Tilt capacity from -5° to 90°
- > Dual inputs: VGA and DVI
- > HID compliant for easy integration
- > Optional RJ11 wired OSD external remote control
- > Lockable OSD setting to provide security when used in public spaces
- > Rugged base design for superb stability
- > Durable metal housing
- > Rigorous screening of the components for mission-critical 24/7 applications

# TX-15

## Specifications

## TX-15

<b>Panel</b>	Panel Type	LED-Backlit TFT LCD
	Panel Size	15.0"
	Max. Resolution	1024 x 768
	Pixel Pitch	0.297 mm
	Brightness	250 cd/m <sup>2</sup> (Typical)
	Contrast Ration	700 : 1 (Typical)
	Viewing Angle (H/V)	160°/140°
	Disply Colour	16.2 M
Response Time (GTG)	4 ms (GTG)	
<b>Frequency (H/V)</b>	H.Freq	31.5kHz - 60kHz
	V.Freq	56Hz - 75Hz
<b>Input</b>	VGA	15-Pin D-Sub
	DVI	24-Pin DVI-D
<b>External Control</b>	RJ11	RJ11
<b>Touch Screen</b>	Technology	Projected Capacitive
	Positioning Accuracy	±2.5mm
	Active Force	Non-required
	Panel Interface	USB (Type-B, HID compliant)
<b>Power</b>	Power Supply	External
	Power Requirements	DC 12V
	Consumption	< 15W (On)
		< 2W (Stand-by)
< 1W (Off)		
<b>Operating Conditions</b>	Temperature	0°C ~ 40°C (32°F~104°F)
	Humidity	10% ~ 80% (No condensation)
<b>Storage Conditions</b>	Temperature	-20°C ~ 60°C (-4°F~140°F)
	Humidity	10% ~ 90% (No condensation)
<b>Mounting</b>	VESA FPMPI	Yes (100 x 100mm)
<b>Dimensions</b>	with Base (W x D x H)	348 x 313 x 214 mm (13.7" x 12.3" x 8.4")
	w/o Base (W x H x D)	348 x 276 x 47 mm (13.7" x 10.9" x 1.9")
	Packaging (W x H x D)	415 x 290 x 370 mm (16.3" x 11.4" x 14.6")
<b>Weight</b>	Product Weight (with base)	4.6 kg (10.1 lbs)
	Packaging weight	7.0 kg (15.4 lbs)
<b>Regulation Approval</b>	Certifications & Compliance	CE, RoHS, WEEE, REACH
<b>Accessories</b>	Supplied	CD ROM (user manual and touch driver), 15-Pin D-Sub cable, power cord, power adaptor, USB cable, cable cover and screw, warranty card



Integration of 10-point touch and projected capacitive touch technology provides accurate and precise touch experience



Wide range of tilt flexibility from -5° to 90°



A rating of IP65 attests to its extraordinary protection against dust and liquid



Durable metal housing and the whole enclosure designed with IPX1 level for drip-proof

