













CAMERA FEATURES >

The versatile Vulcan™ Series HD-V camera from AngelTrax features a fully articulated lens casing, adjustable vertically, horizontally and 180 degrees in any direction at installation, to obtain the desired view of the vehicle's interior or exterior and surroundings. Each HD-V camera features a built-in noise-gated microphone for interior applications or can be IP68 rated waterproof for use as an exterior camera. Equipped with Super Infrared, automated white balance and digital noise reduction, Vulcan Series HD-V cameras are capable of capturing astonishingly clear high-definition images day or night.

HD-V SERIES TECH SPECS ▼

LENS

- 3MP
- CMOS Sensor
- Fully articulated lens casing for image orientation

MAIN STREAM RESOLUTION

• 1920 x 1080 @ 25/30fps

IMAGE CONTROL

- Digital Wide Dynamic Range (DWDR)
- Automated White Balance (AWB)
- Automatic Gain Control (AGC)

INFRARED

- · Super IR circuit design for auto-exposure control when IR is ON
- Super IR: 98 164 feet

DAY OR NIGHT

External sensor for auto switch between day and night modes

<u>AUDIO</u>

· Built-in noise-gated microphone

HD1700V

- 1.7mm Lens
- Extremely Wide Angle
- Shorter Focal Length
- 170° Horizontal FOV
- 90° Vertical FOV





> HD1700V includes lens bracket designed to ensure optimal view of passenger seating.

HD2100V

- 2.1mm Lens
- Super Wide Angle
- Shorter Focal Length 125° Horizontal FOV

125°



HD2500V

- 2.5mm Lens
- Super Wide Angle
- Shorter Focal Length
- 110° Horizontal FOV

110°

HD3600V

3.6mm Lens

- Wide Angle
- Medium Focal Length
- 70° Horizontal FOV



HD6000V

- 6.0mm Lens
- Narrow Angle
- Deeper Focal Length

52° Horizontal FOV

For full camera specifications, visit angeltrax.com





6/2024 - Specifications, features and applications of use are subject to change without notice. Copyright © 2024 • IVS, Inc. dba AngelTrax • All Rights Reserved

