*A*RITECH

COVERT CAMERA

COLOUR

EV 400/CSA

EV 400 detector case containing colour camera with standard lens and audio

One of a range of PIR cameras designed for the professional security installer using the latest miniature camera technology.

- An ideal camera for detecting rather than deterring crime
- **Excellent picture quality**
- Discreet, stylish case designed to blend inconspicuously into any commercial environment
- Ideal for use where EV 400 detectors are already installed
- Comes with pre-focused (1m ∞) factory-fitted lens
- Ideal for the video verification of alarms
- Simple and speedy to install
- Comes with versatile wall or ceiling mount bracket for exact camera positioning
- Standard lens views through clear viewing window for improved performance in low light conditions
- Scratch-resistant camera viewing window for easy maintenance
- Comes with free audio capability
- Comes with lint-free cleaning cloth to remove grease and dirt from case and lens



1/4" CCD




350 TV lines



5.0 lux sensitivity



Supply voltage: 12 Vdc Audio output: 1V p-p



See Also:



EV 400/MSA Monochrome version



EV 400/MPA Monochrome pinhole version



EV 500/MPAW Monochrome pinhole camera inside working EV 500 PIR

SPECIFICATION	MOD-607 camera module
Image sensor	1/4" CCD sensor, 500 (H) x 582 (V) pixels
Horizontal resolution	350 TV lines or greater
Lens options	SEE TABLE
Electronic shutter	Automatic linear shutter
Sensitivity	5.0 lux
Video output	PAL, 1Vp-p, 75 Ohms
Supply voltage	12 Vdc <u>+</u> 10%
Working temperature	-5°C to +40°C
Microphone	Omni-directional electret
Audio output	1Vp-p, 600 Ohms

0	Microphone	Omni-directional electret
D	Audio output	1Vp-p, 600 Ohms
A	Audio bandwidth	100Hz - 10KHz, +/- 3dB