

COVERT CAMERA
MONOCHROME

EV 400/MPA

- EV 400 detector case containing monochrome camera with pinhole lens and audio

One of a range of PIR cameras designed for the professional security installer using the latest miniature camera technology.

- An ideal camera for detecting rather than deterring crime
- Excellent picture quality
- Discreet, stylish case designed to blend inconspicuously into any commercial environment
- Ideal for use where EV 400 detectors are already installed
- Camera views through tiny 1.5mm diameter hole for maximum discretion
- Comes with pre-focused (1m - ∞) factory-fitted lens
- Ideal for the video verification of alarms
- Simple and speedy to install
- Comes with versatile wall or ceiling mount bracket for exact camera positioning
- Comes with free audio capability
- Comes with lint-free cleaning cloth to remove grease and dirt from case and lens



- 1/3" CCD
- 380 TV lines
- 3.0 lux sensitivity
- Supply voltage: 12 Vdc
- Audio output: 1V p-p

Lens options

Lens	Product Code
3.6mm pinhole	EV 400/MPA
5.5mm pinhole	EV 400/MPA/5.5

All lens options are the same price

See Also:



EV 400/CPA
Colour version



EV 400/CSA
Colour standard
lens version



EV 500/MPAW
Monochrome
pinhole camera
inside working EV
500 PIR

SPECIFICATION

	MOD-308/PA camera module
Image sensor	1/3" CCD sensor, 512 (H) x 582 (V) pixels
Horizontal resolution	380 TV lines or greater
Lens options	SEE TABLE
Electronic shutter	Automatic linear shutter
Sensitivity	3.0 lux
Video output	CCIR, 1Vp-p, 75 Ohms
Supply voltage	12 Vdc ± 10%
Working temperature	-18°C to +60°C

VIDEO

Microphone	Omni-directional electret
Audio output	1Vp-p, 600 Ohms
Audio bandwidth	100Hz - 10KHz, +/- 3dB

AUDIO