

## KM-12 12" Monochrome 4-Channel Monitor Kit

- 4 camera switcher built in
- Manual and automatic camera selector
- Alarm inputs/outputs
- Built-in two-way audio capability
- Camera has electronic auto iris for any lighting condition
- BNC connectors available for alternative inputs camera
- VCR output
- Camera has built-in infrared illumination for low-light conditions



### → Technical data

Picture	12" B/W CRT sensor
System	CCIR
Power source	110 - 220 - 230 - 240 V ac
Resolution	Over 800 lines at centre
Connection	
Camera	6 pin mini Din jack
Output slave A/V	2 RCA connectors
Alarm output	3 pin terminals
Alarm input	5 pin terminals
Alarm time	15 sec (fixed)
Video input impedance	1.0 V p-p, 75 Ohm
Video output	1.0 V p-p, 75 Ohm
Frequency	
Horizontal	15.625 KHz
Vertical	50 Hz
Power consumption	50 W
Operating temperature	-10° to +50° C
Dimensions	320 x 320 x 310 mm (H x W x D)
Weight	7 kg

**→ How to order**

KM-12	12" monochrome 4-channel monitor kit, incl. camera, bracket, 20 m cable
KM-C104	1/3" monochrome extra camera kit, incl. camera, bracket, 20 m cable
KCAB-20	20 m of extension cable (max. 100 m per camera)

**Interlogix UK Limited**

Unit 5, Ashton Gate,  
Ashton Road, Harold Hill,  
Romford, Essex RM3 8UF  
Tel. 01708-381496  
Fax 01708-381371

[www.aritech.com](http://www.aritech.com)

**Interlogix Ireland Limited**


Taurus Business Centre  
Greenhills Road  
Tallaght, Dublin 24  
Tel. 01-459.97.60  
Fax 01-452.74.48

**Interlogix Europe & Africa**

Headquarters  
Excelsiorlaan 28  
B-1930 Zaventem  
Tel. 02-725 11 20  
Fax 02-721 40 47

**Sales Offices :** Austria, Baltic States, Belgium, Czech Republic, Denmark, Eastern Europe, France, Germany, Greece, Hungary, Ireland, Italy, Netherlands, Norway, Poland, Portugal, Slovak Republic, South Africa, Spain, Sweden, U.K.

LFKM-12 03 Rev.2 0701/UK

 Aritech reserves the right to change specifications without notice.  
Aritech is a trademark of Interlogix B.V.