



Accu-Time Systems, Inc.

Series 3000

The Accu-Time **Series 3000** is the benchmark for full-function data collection terminals. "C" programmable and feature-rich, the **Series 3000** is ideally suited in small or large employee based companies. Collecting payroll? Employee scheduling? Processing or storing critical employee data? The Accu-Time **Series 3000** -- A product with answers.

- ▶ Single or multi-clock environments
- ▶ 64K Byte memory base (capacitor backed)
- ▶ EIA Standard RS232 or RS485 compatible
- ▶ Integrated and/or external bar code reader
- ▶ Integrated magnetic slot readers
- ▶ Digital bar code wand port
- ▶ Touch memory support
- ▶ Relay and printer interface modules
- ▶ Low voltage power source (local or remote)
- ▶ Die cast aluminum housing w/lockable base



ENTER

Accu-Time Systems, Inc.

t: 860.870.5000

f: 860.872.1511

www.accu-time.com

ACCU-TIME®

Series 3000

Specifications

DISPLAY	2 or 4 line x 20 character super-twist LCD (backlit option available) 2 line x 20 character Vacuum Fluorescent
CLOCK	12 or 24 hour format — USA or International (quartz precision) Time stamp of data transactions
INDICATORS	Yellow LED low power indicator Red and green programmable LED indicators
KEYPAD	Software defined function keys Large 20 key tactile 4x5 matrix Custom user-defined keypad legends
BEEPER	Audible annunciator
MEMORY	64K Byte of capacitor backed memory (i.e. 300-employee base — program dependent)
PROGRAMMING	ATS DATA TRAKER™ modules, C programming language or third party custom application packages
SELF-TEST	ACCURATE™ on-board terminal set-up and full-feature diagnostics
INTERFACE	EIA Standard RS232 or RS485 (2 or 4 wire) Standard AT Command Set for internal 12/2400 Baud modem
ENCLOSURE	Die cast aluminum housing with steel key-lockable base assembly
POWER	+10 to +17VDC (+12VDC @ 250 milliamps Nominal) Local, remote or centrally powered Non-interruptible power source with charger (optional)
ENVIRONMENT	Operation: 32° to 110°F (0° to 43°C)
CERTIFICATION	CE Mark Certified (CE, RE, ESD, RS and CS), FCC part 15
PHYSICAL	7.0" L x 7.25" W x 3.4" H Weight: 4 lbs. (17.78 cm L x 18.42 cm W x 8.64 cm H Weight: 1.8 kg)
ACCESSORIES	Integrated or external optical bar code slot reader Integrated magnetic slot readers Digital bar code wands, touch memory option External wand emulation bar code laser and CCD readers Auxiliary relay or printer interface port



Accu-Time Systems, Inc.
One Accu-Time Plaza
420 Somers Road
Ellington, CT 06029
1-800-355-4648
Tel: (860) 870-5000
Fax: (860) 872-1511
E-mail: sales@accu-time.com

Accu-Tech Systems LLC
26 Orion Suite
Enterprise Way
Newport, U.K. NP20 2AQ
Tel: +44-1633-84-0000
Fax: +44-1633-84-1000

www.accu-time.com

Accu-Time, whose policy is one of continuous improvement, reserves the right to change specifications without notice.