

| | | | |
|-------------------------------|-------------------------|------------------|------------------------------|
| Model No. | | HZCA08551 | |
| Image Format Cover | | 1/2" ~ 1/3" | |
| Focal Length | | 8.5 ~ 51mm | |
| Maximum Aperture Ratio | | 1:1.2 | |
| Zoom Ratio | | 6X | |
| Iris | Control Method | | Video Drive |
| | Iris Range | | F1.2 ~ 360 |
| | Speed | | Approx. 2 sec |
| | Input Voltage & Current | | DC8 ~ 16V Max.30mA |
| | Sensitivity Adjustment | | 0.5 ~ 1.0Vp-p |
| Focus | Control Method | | Motorized |
| | Speed | | Approx. 2.5 sec |
| | Input Voltage & Current | | DC12V Max.50mA |
| Zoom | Control Method | | Motorized |
| | Speed | | Approx. 2 sec |
| | Input Voltage & Current | | DC12V Max.50mA |
| Angle Field of View (DXHXV) | 1/3 inch | Wide | 38.8°X31.3°X23.6° |
| | | Tele | 6.8°X5.5°X4.1° |
| | 1/2 inch | Wide | 50.7°X41.2°X31.3° |
| | | Tele | 8.9°X7.2°X5.5° |
| Minimum Object Distance | | | 1.1m |
| Back Focal Length | | | 12.55mm |
| Effective Diameter | Front | | ø44.0mm |
| | Rear | | ø11.7mm |
| Filter Screw Size | | | M52.0 P=0.75 |
| Mount / Flange Back | | | C/17.526 |
| Mechanical Dimension (WXHXL) | | | 66.0mmX82.5mmX93.4mm |
| Total Weight | | | 610.0g |
| Application Temperature Range | | | 0°C ~ +50°C (+32°F ~ +122°F) |
| Remarks | | | --- |

