

| | | | |
|-------------------------------|-------------------------|--------------------------------|--|
| Model No. | | TTSG0612 | |
| Image Format Cover | | 1/3" | |
| Focal Length | | 6.0mm | |
| Maximum Aperture Ratio | | 1:1.2 | |
| Iris | Control Method | Video Drive | |
| | Iris Range | F1.2 ~ 360 | |
| | Speed | Approx. 1.5 sec | |
| | Input Voltage & Current | DC8 ~ 16V Max.30mA | |
| | Sensitivity Adjustment | 0.5 ~ 1.0Vp-p | |
| Focus | Control Method | Manual | |
| Angle Field of View (DXHXV) | 1/4 inch | 43.4°X34.4°X25.7° | |
| | 1/3 inch | 61.1°X48.1°X35.6° | |
| Minimum Object Distance | | 0.3m | |
| Back Focal Length | | 9.30mm | |
| Effective Diameter | Front | ø14.0mm | |
| | Rear | ø8.9mm | |
| Filter Screw Size | | --- | |
| Mount / Flange Back | | CS/12.5mm | |
| Mechanical Dimension (DXHXL) | | ø32mmX43.9mmX29.5mm | |
| Total Weight | | 48.7g | |
| Application Temperature Range | | -10°C ~ +50°C (+14°F ~ +122°F) | |
| Remarks | | --- | |

