

| | | | |
|--------------------------------|-------------------------|--------------------|--------------------------------|
| Model No. | | TVSG2510 | |
| Image Format Cover | | 1/3" ~ 1/4" | |
| Focal Length | | 2.5 ~ 10mm | |
| Maximum Aperture Ratio | | 1:1.4-2.7 | |
| Zoom Ratio | | 4.0X | |
| Iris | Control Method | Video Drive | |
| | Iris Range | F1.4(2.7) ~ 360 | |
| | Speed | Approx. 1.5 sec | |
| | Input Voltage & Current | DC8 ~ 16V Max.30mA | |
| | Sensitivity Adjustment | 0.5 ~ 1.0Vp-p | |
| Focus | Control Method | Manual | |
| Zoom | Control Method | Manual | |
| Angle Field of View (DXHXV) | 1/4 inch | Wide | 99.2°X79.5°X59.6° |
| | | Tele | 26.6°X21.3°X16.0° |
| | 1/3 inch | Wide | 130.9°X105.8°X79.5° |
| | | Tele | 35.3°X28.3°X21.3° |
| Minimum Object Distance | | | 0.3m |
| Back Focal Length | | | 9.52 ~ 21.05mm |
| Effective Diameter | Front | ø26.9mm | |
| | Rear | ø8.3mm | |
| Filter Screw Size | | | --- |
| Mount / Flange Back | | | CS/12.5mm |
| Mechanical Dimension (DX(H)XL) | | | ø48mmX50.5mmX60mm |
| Total Weight | | | --- g |
| Application Temperature Range | | | -10°C ~ +50°C (+14°F ~ +122°F) |
| Remarks | | | --- |

