

## **AXIS T92A00 Housing**

Protective housing for Axis network cameras.



- > Indoor and outdoor installation
- > Easy installation
- > Aluminum casing
- > IP66-rated protection
- > Sunshield included

AXIS T92A00 Housing protects the Axis network camera in outdoor and adverse indoor conditions.

AXIS T92A00 Housing is tailor-made and carefully tested to comply with Axis network cameras. This stylishly designed housing has a side opening and a preinstalled power supply for easy and time saving installation.

Made of die-cast aluminum, the AXIS T92A00 Housing offers an IP66-rated protection against dust and heavy rain.

The sunshield with its integrated edge-protector offers good thermal insulation, enabling the Axis network camera to operate in temperatures up to  $+50^{\circ}\text{C}$  ( $+122^{\circ}\text{F}$ ). Lowest operating temperature is  $-20^{\circ}\text{C}$  ( $-4^{\circ}\text{F}$ ).


Various brackets and accessories are available, such as ceiling and wall brackets, column mounts and adapters.

Supported cameras are AXIS 210, AXIS 210A, AXIS 211, AXIS 211A, AXIS 211M, AXIS 211W, AXIS 221 and AXIS 223M Network Cameras.



## Technical specifications – AXIS T92A00 Housing

General	
Supported cameras	AXIS 210*, AXIS 210A*, AXIS 211, AXIS 211A, AXIS 211M, AXIS 211W**, AXIS 221 and AXIS 223M Network Cameras *indoor use only *external antenna required
Casing	Die-cast aluminum Sunshield in ABS Color: White grey RAL9002 3 removable cable glands (2xPG9 & 1xPG11)
Power	230 VAC / 44W
Environment	Indoor/outdoor
Operating conditions	-20°C to + 50°C (-4°F to 122°F)
Protection rating	IP66
Approvals	CE: EN 60950, EN 61000-6-3, EN 50130-4
Weight	3.0 kg (6.6 lb) incl. sunshield
Included accessories	Sunshield, heater and thermostat, installation kit for camera, Installation Guide



## More information and a configuration tool is available at www.axis.com/accessories

