

DAX/DMA  
DAX/JVC  
DAX/MM

DAX/PAN  
DAX/PHIL



### FEATURES

- Easy to install due to its compact size and minimal cabling requirement
- Auto tuning to minimise installation time
- Compatible with most leading dome camera brands
- Up to 16 presets supported per dome camera
- Patrol function available
- Pan flip (Auto flip) function supported on some dome cameras
- Sites can have a selection of AC or DC receivers and DAX converters controlled from one transmitter
- Proportional variable speed supported with the ZKX2/J joystick keyboard

### Supported Domes

Baxall Part Number	Manufacturer	Model
DAX/DMA	Star Micronics Sanyo Computar	MD-100, MD-800, MD-1200S, MD-2000, MD-1200H VCC-9200P SMD-08, SMD-08II, SMD-12, AMD-12II, SMD-20
DAX/JVC	JVC	TK-C675
DAX/MM	Mark Mercer	D250mpT, D4/500mpT, etc.
DAX/PAN	Panasonic	WV-CSR400, WV-CSR600
DAX/PHIL	Phillips	TC7414

### Specifications

<b>Video Input</b>	1V peak to peak 75Ω terminated
<b>Video Output</b>	1V peak to peak 75Ω terminated
<b>Data Comms</b>	RS485, RS422
<b>Power Supply</b>	12V DC less than 50mA (240V AC Plug top supply included)
<b>Dimensions</b>	109 x 58 x 31mm
<b>Colour</b>	Light Grey
<b>Operating temperature</b>	-0°C to +40°C
<b>Storage temperature</b>	-30°C to +100°C

