

DAX/DMA
DAX/JVC
DAX/MM

DAX/PAN
DAX/PHIL



FEATURES

- Easy to install due to its compact size and minimal cabling requirement
- Auto tuning to minimise installation time
- Compatible with most leading dome camera brands
- Up to 16 presets supported per dome camera
- Patrol function available
- Pan flip (Auto flip) function supported on some dome cameras
- Sites can have a selection of AC or DC receivers and DAX converters controlled from one transmitter
- Proportional variable speed supported with the ZKX2/J joystick keyboard

Supported Domes

Baxall Part Number	Manufacturer	Model
DAX/DMA	Star Micronics Sanyo Computar	MD-100, MD-800, MD-1200S, MD-2000, MD-1200H VCC-9200P SMD-08, SMD-08II, SMD-12, AMD-12II, SMD-20
DAX/JVC	JVC	TK-C675
DAX/MM	Mark Mercer	D250mpT, D4/500mpT, etc.
DAX/PAN	Panasonic	WV-CSR400, WV-CSR600
DAX/PHIL	Phillips	TC7414

Specifications

Video Input	1V peak to peak 75Ω terminated
Video Output	1V peak to peak 75Ω terminated
Data Comms	RS485, RS422
Power Supply	12V DC less than 50mA (240V AC Plug top supply included)
Dimensions	109 x 58 x 31mm
Colour	Light Grey
Operating temperature	-0°C to +40°C
Storage temperature	-30°C to +100°C