

## Pyramid 2 keyboard

Part Code: PY2-KBD

The pyramid 2 keyboard is the central control point for the Pyramid system, offering full control of up to 144 cameras including fixed, PTZ and dome cameras with AC and DC control. This keyboard can control up to 32 monitors and 8 serially controlled devices such as multiplexers, VCR's, and hard disk recorders.

The colour coded general purpose soft keys provide an easy to use, menu driven customer interface and the 3-axis joystick facilities precise control of pan, tilt and zoom functions.

The keyboard is smart card protected allowing multiple operators to control the system, this is achieved by defining user priorities for each operator. The smart card also contains a new facility that configures the operator level and subsequently defines the screen configuration being displayed. The four options that are available range from the Basic user, the Advanced User, Supervisor or Installer.

The keyboard also acts as an advanced configuration tool enabling the user to address alarms units, bridges and receivers. It also has the facility to configure Rx functions.

The keyboard has been ergonomically designed with a 100mm x 150mm (4î by 6î) backlit VGA display and tactile, colour coded, elastomeric.



- User friendly operation
- Durable 3-axis PTZ joystick
- Soft key driven menu options
- Large back-lit VGA display
- RS485 and FTT10 network control
- Centralised or distributed control



## **Specifications**

LCD: Size CCFL Backlit VGA 110mm x 150mm (4" x 6")

11 Soft Keys

**CONTROLS:** 

**Keys:** Tactile, Colour coded, Elastomeric Keys

Numeric keypad

Camera/monitor selection

Delete

Next/previous camera

Focus near/far Iris open/close

Screens: 4 User Levels

Joystick: Three Axis joystick for pan, tilt and zoom control

Connections: RJ45 connector for 12V power and duplex RS485 or FTT10

Smart card: Spring loaded card at the rear of the keyboard

Log-on protection allowing multi-level access to all system

**Functions** 

System: Camera and monitor selection

Sequences Auxiliary control PTZ functions Dome control

PHYSICAL:

**Dimensions:** 385 x 190 x 66mm

Weight: 2.4kg

**Construction:** ABS cover on a mild steel base

Colour: Graphite grey

Power: Nominal 6 watts @12v DC

Approvals: C.E.



