



DELL EMC NETWORKING N4000 SERIES SWITCHES

Energy-efficient, cost-effective 10GbE switches for modernizing and scaling network infrastructure

The N4000 switch series offers a power-efficient and resilient 10 Gigabit Ethernet (10GbE) switching solution with support for 40GbE uplinks for advanced Layer 3 distribution for offices and campus networks.

The N4000 switch series has high-performance capabilities and wire-speed performance utilizing a non-blocking architecture to easily handle unexpected traffic loads. The N4000 series includes dual internal hot-swappable 80PLUS-certified power supplies for high availability and power efficiency. The switches offer simple management and scalability via flexible user port stacking at 10Gbps or 40Gbps. The high-availability stacking architecture allows management of up to 12 switches from a single IP address.

Modernize campus network architectures

Modernize campus network architectures with a power-efficient and resilient 10/40GbE switching solution for environments requiring high throughput and availability at the aggregation or core. For greater interoperability in multivendor networks, N4000 series switches offer the latest open-standard protocols and include technology to interface with Cisco protocol RPVST+* and devices using CDP.

Achieve high availability and full bandwidth utilization with Multi-chassis Link Aggregation (MLAG). N4000 series switches support MLAG to create active/active loop-free redundancy without spanning tree. Server rooms can deliver reliable server and storage connectivity with features to help save time and avoid configuration errors. These high density 24-port or 48-port 10GbE switches are ready for converged fabric requirements for SAN and LAN networks with loss-less operation for iSCSI environments with Data Center Bridging (DCB). N4000 supports VRF-lite, allowing it to be partitioned into multiple virtual routers with isolated control and data planes on the same physical switch. The N4000 series is also fully tested and validated to work with Dell EqualLogic™ PS-Series storage arrays.**

Leverage familiar tools and practices

All N-Series switches include Dell Networking OS 6, designed for easier deployment, greater interoperability and a lower learning curve for network administrators. One common command line interface (CLI) and GUI using a well-known command language gets skilled network administrators productive quickly. With USB auto-configuration, network administrators can rapidly deploy mirrored configurations to numerous devices by simply inserting a USB key.

Deploy with confidence at any scale

N4000 series switches help create performance assurance with a data rate up to 1.28Tbps (full duplex) and a forwarding rate up to 952Mpps. Scale easily with 10/40Gbps user port stacking supporting distances up to 100 meters. Switch stacks of up to 672 10GbE ports can be managed from a single screen using the highly-available stacking architecture for high-density aggregation with seamless redundant availability. N-Series switches help provide certainty with a lifetime warranty that covers software upgrades, hardware repair or replacement as well as optics and cables purchased with the switch. Details at Dell.com/LifetimeWarranty***

Hardware, performance and efficiency

- Up to 32 10GbE ports (N4032 and N4032F) and up to 64 10GbE ports (N4064 and N4064F) using breakout cables.
- Converged network support for DCB with Priority Flow Control (802.1Qbb), ETS (802.1Qaz), DCBx, iSCSI TLV Support.
- Up to 672 10GbE ports in a 12-unit stack for high-density, high-availability aggregation and distribution in wiring closets/MDFs. Non-stop forwarding and fast failover in stack configurations.
- Hot swappable expansion module supporting dual-port QSFP+ (8x 10GbE), quad-port 10GBaseT and quad-port SFP+.
- Dual 80PLUS-certified efficient hot swappable power supplies and redundant variable speed fan operation help decrease cooling and power costs.
- Energy-Efficient Ethernet and lower power PHYs reduce power to inactive ports and idle links, providing energy savings from the power cord to the port.
- Dell Fresh Air compliance for operation in environments up to 113°F (45°C) helps reduce cooling costs in temperature constrained deployments.

Deploying, configuring and managing

- Tool-less ReadyRails™ significantly reduces rack installation time.
- USB auto-configuration rapidly deploys the switches without complex TFTP configurations or sending technical staff to remote offices.
- Plug-and-Play configuration with Dell EqualLogic iSCSI storage arrays** and one-command iSCSI setup alleviates multiple step configuration and potential configuration errors.

| Product | Description |
|---------------------------|---|
| N4000 series | <p>N4032F: 24x 10GbE SFP+ auto-sensing (10Gb/1Gb) fixed ports, 1x hot swap expansion module bay, 2x redundant 460W PSU included</p> <p>N4064F: 48x 10GbE SFP+ auto-sensing (10Gb/1Gb) fixed ports, 2x 40GbE QSFP+ fixed ports, 1x hot swap expansion module bay, 2x redundant 460W PSU included</p> |
| Power cords | <p>125V, 15A, 10 feet, NEMA 5-15/C13</p> <p>250V, 12A, 2 meters, C13/C14</p> <p>Country- and region-specific power cord options available</p> |
| Modules (optional) | <p>4-port 10 Gigabit SFP+ hot swappable module</p> <p>4-port 10 Gigabit Base-T RJ-45 hot swappable module</p> <p>2-port 40 Gigabit QSFP+ hot swappable module</p> |
| Optics (optional) | <p>Transceiver, SFP, 1000BASE-T</p> <p>Transceiver, SFP, 1000BASE-SX, 850nm wavelength, up to 550m reach</p> <p>Transceiver, SFP, 1000BASE-LX, 1310nm wavelength, up to 10km reach</p> <p>Transceiver, SFP+, 10GbE, LRM, 1310nm wavelength, up to 220m reach</p> <p>Transceiver, SFP+, 10GbE, SR, 850nm wavelength, up to 300m reach</p> <p>Transceiver, SFP+, 10GbE, LR, 1310nm wavelength, up to 10km reach</p> <p>Transceiver, QSFP+, 40GbE, SR4, 850nm wavelength, up to 150m reach</p> <p>Transceiver, QSFP+, 40GbE, ESR, 850nm wavelength, up to 300m reach</p> <p>Transceiver, QSFP+, 40GbE, LR4, 1310nm wavelength, up to 10km reach</p> <p>Transceiver, QSFP+, 40GbE, PSM4 with 1m, 5m or 15m pigtail to MPO</p> |
| Cables (optional) | <p>Dell Networking cable, SFP+ to SFP+, 10GbE, copper twinax direct attach cable, 0.5m, 1m, 3m, 5m, 7m</p> <p>Dell Networking cable, QSFP+ to 4x SFP+, 40GbE to 4x10GbE, passive copper breakout cable, 0.5m, 1m, 3m, 5m, 7m</p> <p>Dell Networking cable, QSFP+ to QSFP+, 40GbE, passive copper direct attach cable, 0.5m, 1m, 3m, 5m, 7m</p> <p>OM3 MTP fiber cable, QSFP+ to QSFP+, 40GbE, requires QSFP+ optics, 1m, 3m, 5m, 7m, 10m, 25m, 50m, 75m, 100m</p> <p>Fiber breakout cable, QSFP+ to 4x SFP+, 40GbE MTP to 4x 10GbE LC, requires 1x QSFP+ and 4x SFP+ optics, 1m, 3m, 5m, 7m</p> |

Technical specifications

Physical

User port stacking up to 100m using 10Gb or 40Gb supporting up to 160Gbps on N4032 and 320Gbps on N4064 (full duplex)

Rear out-of-band management port (10/100/1000BASE-T)

USB (Type A) port for configuration via USB flash drive

Auto-negotiation for speed and flow control

Auto-MDI/MDIX, port mirroring

Flow-based port mirroring

Broadcast storm control

Energy-Efficient Ethernet per port settings

Redundant variable speed fans

Air flow: I/O to power supply

Dual redundant hot swappable power supplies included: 460W

RJ45 console/management port with RS232 signaling (RJ-45 to female DB-9 connector cable included)

Dual firmware images on-board

Chassis

Size (1RU, H x W x D): 1.71 in x 17.08 in x 18.11 in (43.43 mm x 433.83 mm x 459.99 mm)
(Power supply handle adds 1.13 in or 28.7 mm)

Approximate weight: 21.67lbs/9.83kg (N4032), 21.14lbs/9.59kg (N4032F), 24.07lbs/10.92kg (N4064), 23.28lbs/10.56kg (N4064F)

ReadyRails rack mounting system, no tools required

Environmental

Power supply efficiency: 80% or better in all operating modes

Max. thermal output (BTU/hr): 823.44 (N4032), 603.86 (N4032F), 1353.53 (N4064), 754.82 (N4064F)

Power consumption max (watts): 240 (N4032), 176 (N4032F), 395 (N4064), 220 (N4064F)

Operating temperature: 32° to 113°F (0° to 45°C)

Operating relative humidity: 90%

Storage temperature: -4° to 158°F (-20° to 70°C)

Storage relative humidity: 95%

Performance

MAC addresses: 131,072

Static routes: 1,024 (IPv4)/1,024 (IPv6)

Dynamic routes: 8,160 (IPv4)/4,096 (IPv6)

Switch fabric capacity: 640Gbps (N4032 and N4032F) (full duplex)

1.28Tbps (N4064 and N4064F)

Forwarding rate: 476Mpps (N4032 and N4032F) 952Mpps (N4064 and N4064F)

Link aggregation: 128 LAG groups, 144 dynamic ports per stack, 8 member ports per LAG

Queues per port: 8

Line-rate Layer 2 switching: All (non-blocking)

Line-rate Layer 3 routing: All (non-blocking)

Flash memory: 256MB

Packet buffer memory: 9MB

CPU memory: 2GB

OSPF routing interfaces: 8,160

RIP routing interfaces: 512

ECMP next hops per route: 4

ECMP groups: 1,024

VLAN routing interfaces: 128

VLANs supported: 4,094

Protocol-based VLANs: Supported

Multicast forwarding entries: 512 (IPv4), 256 (IPv6)

ARP entries: 6,144

NDP entries: 1024

Access control lists (ACL): Supported

MAC and IP-based ACLs: Supported
 Time-controlled ACLs: Supported
 Max number of ACLs: 100
 Max ACL rules system-wide: 3,072
 Max rules per ACL: 1,023
 Max ACL rules per interface (IPv4):
 2,047 (ingress), 1,023 (egress)
 Max ACL rules per interface (IPv6):
 1,021 (ingress), 512 (egress)
 Max VLAN interfaces with
 ACLs applied: 24

IEEE compliance

802.1AB LLDP
 Dell Voice VLAN
 Dell ISDP (inter-operates with devices running CDP)
 802.1D Bridging, Spanning Tree
 802.1p Ethernet Priority (User Provisioning and Mapping)
 Dell Adjustable WRR and Strict Queue Scheduling
 802.1Q VLAN Tagging, Double VLAN Tagging, GVRP
 802.1Qaz DCBx, Enhanced Transmission Selection (ETS)
 802.1Qbb Priority-based Flow Control (PFC)
 802.1S Multiple Spanning Tree (MSTP)
 802.1v Protocol-based VLANs
 802.1W Rapid Spanning Tree (RSTP)
 Dell RSTP-Per VLAN (compatible with Cisco's RPVST+)*
 Dell Spanning tree optional features: STP root guard, BPDU guard, BPDU filtering
 802.1X Network Access Control, Auto VLAN
 802.2 Logical Link Control
 802.3 10BASE-T
 802.3ab Gigabit Ethernet (1000BASE-T)
 802.3ac Frame Extensions for VLAN Tagging
 802.3ad Link Aggregation with LACP
 802.3ae 10 Gigabit Ethernet (10GBASE-X)
 802.3AX LAG Load Balancing
 Dell Multi-Chassis LAG (MLAG)
 Dell Policy Based Forwarding
 802.3az Energy-Efficient Ethernet (EEE)
 802.3u Fast Ethernet (100BASE-TX) on management ports
 802.3x Flow Control
 802.3z Gigabit Ethernet (1000BASE-X)
 ANSI LLDP-MED (TIA-1057)
 Dell EqualLogic iSCSI Auto-configuration
 MTU 9,216 bytes
 *Available starting with Dell Networking OS 6.1 release

RFC compliance and additional features

General Internet protocols

General Internet protocols are supported. For a detailed list, please contact your Dell EMC representative.

General IPv4 protocols

General IPv4 protocols are supported. For a detailed list, please contact your Dell EMC representative.

General IPv6 protocols

General IPv6 protocols are supported. For a detailed list, please contact your Dell EMC representative.

Layer 3 functionality

1058 RIPv1 2453 RIPv2
 1724 RIPv2 MIB
 Extension 2740 OSPFv3
 1765 OSPF DB
 overflow 2787 VRRP MIB
 1850 OSPF MIB 3101 NSSA
 2082 RIP-2 MD5
 Auth 3137 OSPF Stub Router
 Advert
 2328 OSPFv2 3623 Graceful Restart
 2338 VRRP 3768 VRRP
 2370 Opaque LSA Option 4271 BGP
 Dell Policy Based Routing 5187 OSPFv3 Graceful Restart

Multicast

1112 IGMPv1 3810 MLDv2
 2236 IGMPv2 3973 PIM-DM
 2365 Admin scoped IP Mcast 4541 IGMP v1/v2/v3 Snooping
 2710 MLDv1 and Querier
 2932 IPv4 MIB 4601 PIM-SM
 2933 IGMP MIB 5060 PIM MIB
 3376 IGMPv3 Dell Static IP Multicast
 Draft-ietf-pim-sm-bsr-05
 Draft-ietf-idmr-dvmrp-v3-10 DVMRP
 Draft-ietf-magma-igmp-proxy-06.txt IGMP/MLD Proxying
 Draft-ietf-magma-igmpv3-and-routing-05.txt
 draft-ietf-idmr-dvmrp-mib-11
 draft-ietf-magma-mgmd-mib-05
 draft-ietf-pim-bsr-mib-06
 IEEE 802.1ag draft 8.1 – Connectivity Fault Management (CFM)
 IEEE 802.1p GMRP Dynamic L2 Multicast Registration

Quality of service

2474 DiffServ Field 2697 srTCM
 2475 DiffServ Architecture 4115 trTCM
 2597 Assured Fwd PHB Dell L4 Trusted Mode
 Dell Port Based QoS Services (TCP/UDP)
 Mode Dell Red/WRED
 Dell Flow Based QoS Services Dell Audio Video

Network management and security

1155 SMIv1 1867 HTML/2.0 Forms
 1157 SNMPv1 with file upload
 1212 Concise MIB extensions
 1213 MIB-II 1901 Community-based
 1215 SNMP Traps SNMPv2
 1286 Bridge MIB 1907 SNMPv2 MIB
 1442 SMIv2 1908 Coexistence
 1451 Manager-to-Manager MIB between
 1492 TACACS+ 2011 IP MIB
 1493 Managed objects 2012 TCP MIB
 for Bridges MIB 2013 UDP MIB
 1573 Evolution of 2068 HTTP/1.1
 Interfaces 2096 IP Forwarding Table
 1612 DNS Resolver MIB MIB
 Extensions 2233 Interfaces Group
 1643 Ethernet-like MIB using SMIv2
 1757 RMON MIB 2246 TLS v1
 2271 SNMP Framework
 MIB

2295 Transport Content
 Negotiation
 2296 Remote Variant
 Selection
 2346 AES Ciphersuites
 for TLS
 2576 Coexistence
 between
 SNMPv1/v2/v3
 2578 SMIv2
 2579 Textual
 Conventions
 for SMIv2
 2580 Conformance
 Statements
 for SMIv2
 2613 RMON MIB
 2618 RADIUS
 Authentication
 MIB
 2620 RADIUS Accounting
 MIB
 2665 Ethernet-like
 Interfaces
 MIB
 2666 Identification of
 Ethernet chipsets
 2674 Extended Bridge
 MIB
 2737 ENTITY MIB
 2818 HTTP over TLS
 2819 RMON MIB
 (groups 1,
 2, 3, 9)
 2856 Text Conv. For
 High Capacity
 Data Types
 2863 Interfaces MIB
 2865 RADIUS
 2866 RADIUS
 Accounting
 2868 RADIUS Attributes
 for Tunnel Prot.
 2869 RADIUS
 Extensions
 3410 Internet Standard
 Mgmt. Framework
 3411 SNMP
 Management
 Framework
 3412 Message
 Processing
 and Dispatching
 3413 SNMP
 Applications
 3414 User-based
 security model
 3415 View-based
 control model
 3416 SNMPv2
 3417 Transport
 Mappings
 3418 SNMP MIB
 3577 RMON MIB
 3580 802.1X with
 RADIUS
 3737 Registry of RMON
 MIB
 4086 Randomness
 Requirements
 4113 UDP MIB
 4251 SSHv2 Protocol
 4252 SSHv2
 Authentication
 4253 SSHv2 Transport
 4254 SSHv2
 Connection
 Protocol
 4419 SSHv2 Transport
 Layer Protocol
 4521 LDAP Extensions
 4716 SECSH Public Key
 File Format
 6101 SSL
 6398 IP Router Alert
 Dell Enterprise MIB
 supporting routing
 features draft-ietf-
 hubmib-etherif-
 mib-v3-00.txt
 (Obsoletes RFC
 2665)
 Dell LAG MIB Support
 for 802.3ad
 functionality
 Dell sflow version 1.3
 draft 5
 Dell 802.1x Monitor
 Mode
 Dell Custom Login
 Banners
 Dell Dynamic ARP
 Inspection
 Dell IP Address Filtering
 Dell Tiered
 Authentication
 Dell RSPAN
 Dell Change of
 Authorization
 Dell OpenFlow 1.3
 Dell Python Scripting
 Dell Support Assist
 HiveManager NG

Regulatory, environment and other compliance

Safety and emissions

Australia/New Zealand: ACMA RCA Class A

Canada: ICES Class A; cUL

China: CCC Class A; NAL

Europe: CE Class A

Japan: VCCI Class A

USA: FCC Class A; NRTL UL; FDA 21 CFR 1040.10 and 1040.11

Eurasia Customs Union: EAC

Germany: GS mark

Product meets EMC and safety standards in many countries inclusive of USA, Canada, EU, Japan, China.

For more country-specific regulatory information, and approvals, please see your Dell representative.

RoHS

Product meets RoHS compliance standards in many countries inclusive of USA, EU, China, and India. For more country-specific RoHS compliance information, please see your Dell representative.

EU WEEE

EU Battery Directive

REACH

Energy

Japan: JEL



Certifications (available or coming soon)

Available with US Trade Agreements Act (TAA) compliance.

N-Series products have the necessary features to support a PCI compliant network topology.

IT Lifecycle Services for Networking

Experts, insights and ease

Our highly trained experts, with innovative tools and proven processes, help you transform your IT investments into strategic advantages.



Plan & Design

Let us analyze your multivendor environment and deliver a comprehensive report and action plan to build upon the existing network and improve performance.



Deploy & Integrate

Get new wired or wireless network technology installed and configured with ProDeploy. Reduce costs, save time, and get up and running fast.



Educate

Ensure your staff builds the right skills for long-term success. Get certified on Dell EMC Networking technology and learn how to increase performance and optimize infrastructure.



Manage & Support

Gain access to technical experts and quickly resolve multivendor networking challenges with ProSupport. Spend less time resolving network issues and more time innovating.



Optimize

Maximize performance for dynamic IT environments with Dell EMC Optimize. Benefit from in-depth predictive analysis, remote monitoring and a dedicated systems analyst for your network.



Retire

We can help you resell or retire excess hardware while meeting local regulatory guidelines and acting in an environmentally responsible way.

Distributed by

BCDV IDEO™

FOR MORE INFORMATION: bcdvideo.com | sales@bcdvideo.com | +1.847.205.1922

TECH SUPPORT: support@bcdvideo.com | +1.844.462.2384

This document is provided for information purposes only. The contents are subject to change without notice.

© 2017 Dell Inc. All rights reserved. Dell, the DELL logo and the DELL badge are trademarks of Dell Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. This document is for informational purposes only. Dell reserves the right to make changes without further notice to the products herein. The content provided is as-is and without expressed or implied warranties of any kind. Additional features may be supported and not listed. For a detailed list, please contact your Dell representative.

May 2017 | v3.1

Dell EMC Networking N4000 Series Spec Sheet

DELL EMC