BCD226X-PVS

Professional 2U 26-Bay Rackmount Video Recording Server

MAXIMUM STORAGE DENSITY VIDEO SERVER BUILT FOR PROFESSIONAL PROJECTS

Benefit from next-generation video data archiving and processing with the professional BCD226X-PVS 2U 26-Bay rackmount server. With up to 364TB of raw storage, this video server will be a long-term storage solution for the most demanding of projects.

Powered by (2) of the latest Intel[®] Xeon[®] Silver Scalable Processors, the BCD226X-PVS ensures performance. Memory bandwidth is readily available (16) DIMM slots for up to 512GB of RDIMM memory, ensuring system resources are always available for high intensity applications.

System reliability is at the forefront, with (2) 1100W redundant, hot swappable power supplies, as well as RAID 5/6 storage options to helppreserve data integrity and keep performance at the forefront, while a five-year, on-site, next business day, Keep Your Hard Drive warranty ensures peace of mind.





KEY FEATURES



FOR MORE INFORMATION: <u>bcdvideo.com</u> | <u>sales@bcdvideo.com</u> | +1.847.205.1922 TECH SUPPORT: <u>support@bcdvideo.com</u> | +1.844.462.2384

BCD226X-PVS R1.0 Copyright © 2020, BCDVideo. All rights reserved. This document is provided for information purposes only.

BCD226X-PVS

Professional 2U 26-Bay Rackmount Video Recording Server

SYSTEM

Operating System Windows Server 2019

Memory

Standard Configuration: 32GB (4x 8GB) Maximum Configuration: Up to 512GB RDIMM, 1TB LRDIMM (16x DDR4 DIMM Slots)

Processor(s)

(2) Intel® Xeon® Silver 4216 Scalable Processors (16 Cores, 32 Threads, 3.20GHz)

Processor Passmark Dual Intel® Xeon® Silver 4216: 20,362

Networking (2) 1GbE RJ45 Ports, (2) 10GbE SFP+ ports

Expansion Slots (1) PCle x16 low-profile slot (in default configuration)

USB(s) Rear (2) USB 3.0, Front (1) USB 3.0, Internal (1) USB 3.0

Video Outputs (1) VGA

Remote Management iDRAC Express

MECHANICAL

Form Factor 2U Rackmount

Rack Support Sliding Rack Rail with Cable Management Arm

Power Supply(s) (2) 1100W (100-240VAC) 80 Plus Platinum

Maximum Power Draw 960W

Operating Temperature (Min) 50°F - (Max) 95° F [(Min) 10°C - (Max) 35° C]

Operating Humidity 5 ~ 90% (non-condensing)

Dimensions (WxDxH) 19" (482.6mm) x 33.26" (844.83mm) x 3.4"

Max. Weight 88.18 lbs. (40 kg)

(86.8mm)

Warranty

5-Year, On-site, NBD, Keep Your Hard Drive Warranty

Manufacturer BCDVideo

STORAGE

Hard Drive Bays (26) 3.5" Hot Swappable Bays, (2) M.2 SSD Slots

Hard Drives Supported PCIe NVMe & SATA

RAID OS RAID 0, 1; Data RAID 0, 1, 5, 6, 10

RAID Controller PERC H740P (8GB NV Cache)

Maximum Storage Up to 364TB

FOR MORE INFORMATION: <u>bcdvideo.com</u> | <u>sales@bcdvideo.com</u> | +1.847.205.1922 TECH SUPPORT: <u>support@bcdvideo.com</u> | +1.844.462.2384

BCD226X-PVS R1.0 Copyright © 2020, BCDVideo. All rights reserved. This document is provided for information purposes only.