## TITAN NETWORKING SERIES

SIMPLE, UNICAST NETWORKING



The Titan Networking Series is a series bringing simple, enterprise networking solutions for your security project. Powered by Avaya Networking, the 3524 Family offers a 28 port, stackable solution. The BCD-TTN-3524 is designed in mind for smaller projects with compact solutions. Built for unicast networking, these switches also have a limited lifetime warranty and 24/7 phone support. BCDVideo and Avaya - bringing simple solutions to the security market.

## TTN-3524 FAMILY

## **KEY FEATURES**



PORT DENSITY: 28 PORTS



LIMITED LIFETIME



STACKABLE CHASSIS



UNICAST NETWORKING







solution, the BCD-TTN-3524 provides stackable unicast switches. The series is perfectly suited to the unique requirements of the security market.

	RJ45 PORTS	COMBO SFP PORTS	WEIGHT	INPUT CURRENT (MAX)	Power Consumption
BCD-TTN-3524	24 Gigabit ports	4 Combo SFP	7.8 lb/3.55 kg	.028@100VAC	28.5 Watts (max)
BCD-TTN-3524-POE+	24 Gigabit PoE+	4 Combo SFP	10.2 lb/4.61 kg	5.0A@100VAC	500 Watts (max)

	THERMAL RATING (OUTPUT)	MAXIMUM POE BUDGET	MTBF	UPC
BCD-TTN-3524	95 BTU/hr (max)	N/A	657,619 hrs	859407006142
BCD-TTN-3524-POE+	357 BTU/hr (max)	370 Watts	336,357 hrs	859407006159





## TITAN NETWORKING SERIES

SIMPLE, UNICAST NETWORKING

SYSTEM CPU SPEED 400MHz SYSTEM MEMORY

32MB Flash,
128MB DRAM

INPUT POWER

SWITCH FABRIC PERFORMANCE
52Gbps

FRAME
FORWARDING RATE
38.7Mpps

REAR STACKING

Capable

**CHASSIS**1U Rackmount

**HEIGHT**1.75"/44.5 mm

**WIDTH** 17.5"/440 mm

**DEPTH**11"/280 mm

ENVIRONMENTAL SPECIFICATIONS	SAFETY AGENCY APPROVALS		
Operating Temperature: 32° and 122° F (0° and 50° C)	IEC 60950 International CB Certification		
Operating Altitude: 10,000 ft	EN 60950 European Certification		
Storage Temperature: -40C to 70C	UL60950 US Certification		
Storage Altitude: 10,000 ft	CSA22.2, #60950 Canadian Certification		
Acoustic Noise (db): up to 58 (0 for Fanless models)	NOM Mexican Certification		
Operating Humidity: 95% RH non-condensing			
Storage Humidity: 95% RH non-condensing			



