

BC7009AVAIR12/24R

Dual Voltage Vari-focal IR RS485 Dome Camera



Features:

- 1/3" Super HAD CCD II high resolution DSP
- Color: 600TVL, B/W: 700TVL
- 3 different day/night modes with delay time
- Motion detection and 4 programmable privacy masking
- Digital Wide Dynamic Range (WBLC)
- Advanced Digital Noise Reduction (DNR)
- Advanced High Light Compensation (HLC)



Specification:

Model Number	BC7009AVAIR12/24R
Imaging Sensor	1/3" Sony Super HAD CCD
Effective Pixel	768(H) x 494(V)
Signal System	NTSC
Shutter Speed	1/60 ~ 1/100000s
S/N Ratio	More than 50dB (AGC OFF)
Video Output	1.0 Vp-p, 75 ohm
Resolution	Color: 600TVL, Mono: 700TVL
Minimum Illumination	Color: 0.3 lux, Mono: 0 lux (IR On)
OSD	English
Day/Night	Auto, Color, B/W, External Control
Day/Night Switch Time	3s - 12s Optional
Title Setting	16 characters
IR Leds	30pcs, 850 nm
IR Distance	up to 120ft
Image Brightness	0-100 Adjustable
AGC	0db - 33db
BLC	On/Off, 0-50 Adjustable
WBLC	60dB, 80dB or 100dB
RS485	Support +/-
RS485 Address	1-255
Protocol	Pelco D, 2400/9600/19200
Privacy Masking	up to 4
Operating Temperature	-14°F ~ 120°F, 20-80%
Power Voltage	12VDC/24VAC, 2.5w
Dimension	150Ømm x 95mm

For more information or technical support, please call (909) 305-8889 or log on to www.bolideco.com

468 South San Dimas Avenue, San Dimas CA 91773 | Tel: (909) 305-8889 Fax: (909) 305-0999

Bolide Technology Group makes no representation concerning the legality of certain product application. We encourage you to check and comply with all applicable local state, and federal laws. Specification and availability are subject to change without notice. All trademarks, registered trademarks, and names are the property of their respective owners.