

# **DVR4C Series Digital Video Recorder**



- ► 4-Channel video and audio
- ► Real-time recording
- Small file sizes for extended recording
- Simultaneous recording and playback
- ► Easy local archiving via USB
- Remote viewing, playback and control

Never miss a beat in your retail store, gas station, bank, parking lot or warehouse. The DVR4C digital video recorder from Bosch lets you watch every corner, hallway, door or aisle. This high performance, economical system provides continuous video and audio recording from four cameras plus alarm handling, motion detection and local archiving. This means you are never totally alone because the DVR4C works alongside you as your round-the-clock surveillance partner.

DVR4C puts the emphasis on uninterrupted real-time recording from each of the four cameras, even while you are playing back earlier recordings. Thanks to advanced encoding techniques with very small file sizes, DVR4C captures weeks and weeks of activity, giving you reliable, continuous surveillance with no downtime.


Despite all this power, it's easy to search for specific dates, times, alarms or motion with the built-in intelligent search capability.

Video and audio are archived quickly and conveniently using the built-in USB port to a USB memory stick. And if a recording might be required as legal evidence, it is essential that the recording includes embedded proof of authentication. DVR4C recordings cannot be altered in any way without detection, so the integrity of recordings is guaranteed.

Remote access is available using standard analog or digital telephone lines, over a standard LAN/WAN or Internet connection.


Yet the DVR4C is quick to install and easy to operate, making it ideal for a host of small business applications such as retail stores, banks, gas stations and parking lots.

### **Installation/Configuration Notes**




DVR4C with four cameras, microphone and monitor.

- 1 Cameras
- 3 DVR4C Digital Video Recorder
- 2 Monitor
- 4 Microphone (with line amplifier)



Connections on backside of DVR4C

01	Power switch	06	Monitor output
02	Audio inputs	07	Audio output
03	Camera inputs	08	Relay outputs
04	RS232 connector	09	Alarm inputs
05	Network connector		



# DVR4C Typenumber

01	Type	03	Size per disk in GB
02	Number of disks	04	Revision

# **Parts Included**

Quantity	Component
1	DVR4C
1	DVR4C remote software

# **Technical Specifications**

### **Electrical**

Electrical	
Rated Voltage and Power	
	100 - 240 VAC; 0.7 - 0.3 A; 50 / 60 Hz
Video	
Video Standard	PAL / NTSC auto-detect
Live Resolution	720 x 576 PAL – 720 x 484 NTSC
Digital Zoom	2 times
Compression	MPEG4-based
Inputs	Composite video 0.5V – 2Vpp, 75 ohm
Output	1Vpp, 75 ohm
Audio	
Inputs	Mono RCA, 1.0Vpp
Output	Mono RCA, 1.0Vpp
Alarm Handling	
Inputs	4 Inputs configurable NO/NC, max input voltage 40VDC.
Outputs	4 Relay outputs, configurable NO/NC, max. rated 30VAC-40VDC-0,5A
Control	
RS232	Output signals according EIA/TIA-232-F, max. input voltage $\pm 25 \text{V}$
Connectors	
Video Inputs	4 Looping BNC, manual termination
Monitor	1 BNC
Audio Inputs	4 Cinch
Audio Output	1 Cinch
Ethernet	RJ45S modular jack 8 pins shielded: 10/100 Base-T according IEEE802.3
RS232	DB9 Male
USB	Type A Connector
Alarm I/O	Screw terminal
Storage	
Size	80 - 160 - 320 - 600 GB
Bitrates (per camera at 2	5/30 IPS)
Low	250 kbps
Standard	500 kbps
Medium	750 kbps
High	1 Mbps
Superior	1.5 Mbps
Video recording	
Record Rate (IPS)	
NTSC	120 total, configurable: 30, 15, 7.5, 4, 2, 1, 0
PAL	100 total, configurable: 25, 12.5, 6, 3, 1.5, 0.75, 0
Recording Resolution	352 x 288 PAL – 352 x 240 NTSC

Rated Voltage and Power				
Display Modes				
Monitor	Full, full sequence, quad, alarm call-up			
Recording Modes	Linear, Continuous			
Audio recording				
Compression	ADPCM			
Quality	32 kbps, 8 kHz sampling			
Audio/Video Synchronisation	Best effort, typically <0,5s offset			
USB				
USB Version	1.1			
Supported Media	USB Memory Stick			
Mechanical				
Dimensions	369 x 270 x 83 mm (14.5 x 10.6 x 3.3 inch)			
Weight Approx.	with 1HDD 4.5 kg (9.9 lbs) with 2HDDs 5 kg (11 lbs)			
Environmental				
Temperature				
- Operating	+5°C to +40°C (+41°F to +104°F)			
- Storage	-25°C to +70°C (-13°F to +158°F)			
Humidity				
- Operating	<93% non-condensing			
- Storage	<95% non-condensing			
Electromagnetic compati	ibility			
EMC requirements				
- USA	FCC Part 15, Class B			
- EU	EMC Directive 89/336/EEC			
	Immunity: EN50130-4			
	Emission: EN55022 Class B			
	Harmonics: EN61000-3-2			
	Voltage fluctuations: EN61000-3-3			
Safety				
- USA	UL60950 3rd edition			
- EU	CE, EN60950 2000 3rd edition			
- Can.	CAN/CSA-E60065-00			
PC requirements - remote software				
Operating System	Windows 2000 Professional, XP			
Processor	PIII 600MHz (PIV 2GHz Recommended)			
RAM Memory	128MB (256MB Recommended)			

Video System	16MB Memory, 1024x768 Resolution (64MB Memory Recommended)
Connection	10/100 Base-T network interface

Ordering Information	
DVR4C0001 Digital Video Recorder - APR 4 channel, no HDD	DVR4C0001
DVR4C1081 Digital Video Recorder 4 channel, 80 GB	DVR4C1081
DVR4C1161 Digital Video Recorder 4 channel, 160 GB	DVR4C1161
DVR4C2161 Digital Video Recorder 4 channel, 320 GB	DVR4C2161
DVR4C2301 Digital Video Recorder 4 channel, 600 GB	DVR4C2301
DVR4C1081U Digital Video Recorder 4 channel, 80 GB (UK version)	DVR4C1081U
DVR4C1161U Digital Video Recorder 4 channel, 160 GB (UK version)	DVR4C1161U
DVR4C2161U Digital Video Recorder 4 channel, 320 GB (UK version)	DVR4C2161U
DVR4C2301U Digital Video Recorder 4 channel, 600 GB (UK version)	DVR4C2301U
DVR4C0001C Digital Video Recorder 4 channel, no HDD, Chinese	DVR4C0001C

Free Disk Space

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

10MB

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Asia-Pacific:
Bosch Security Systems Pte Ltd
38C Jalan Pemimpin
Singapore 577180
Phone: +65 6319 3450
Fax: +65 6319 3499
apr.securitysystems@bosch.com
www.boschsecurity.com