TC9320 Series Indoor/Outdoor Designer Domed Housings

- For Cameras With Pan/Tilts
- Tamperproof Fasteners
- Stylish Design
- Tinted or Clear Dome Models
- Optional Rotating Inner Liner
- Accessories Available

The TC9320 Series are attractively designed 500-mm (20-inch) diameter domed housings for use in a variety of CCTV applications including banks, hotels, and private estates. The top portion of the dome is formed from white plastic; the lower capsule is made of 1/8-inch smoked acrylic to conceal the camera's position. The aluminum pendant and threaded coupling are painted black. A quick release mounting bracket (included) for the pan/tilt assembly allows for fast, easy servicing. Optional heater, blower/thermostat assemblies, and a rotating inner-liner are available.



SPECIFICATIONS

Models

 Model No.
 Description

 TC9320
 Tinted dome (1 f-stop light reduction).

 TC9320L
 Tinted dome with rotating inner liner (1 f-stop light reduction).

 TC9320C
 Clear dome (no light reduction).

Mechanical

Maximum Camera/Lens Size: Accepts camera/lens combinations up to 330 L x 102 W x 92 H mm (13 x 4 x 3.6 in).

Cable Entry: Through top of dome.

Housing Mounting: Includes a 1 1/2-inch ID ceiling coupling for pendant mounting. See **Accessories** for wall mounting.

Pan/Tilt and Camera Mounting: Internal quick-release mounting plate for attaching pan/tilt and camera/lens assembly to housing.

Construction/Finish:

Upper Section: Off-white UV protected plastic with black interior.

Lower Section: UV protected high-impact cell-cast acrylic. Clear or tinted depending on model.

Dimensions: See **Dimensional**

Outline.

Weight: 12 kg (27 lb).


Environmental

Temperature: -40 °C to +48 °C (-40 °F to +120 °F).

Accessories

See Accessories for Domed Housings Data Sheet.

Compatible Pan/Tilt Models: LTC 9418 Series, LTC 9420 Series, TC6270PT, TC6270PT-24, and TC6280PT-24.





Suggested Applications

Camera Models¹

Suggested Lenses

 TC360 Series
 Fixed, TC9948A, TC1848B²

 TC380 Series
 Fixed, TC9948A, TC1848B²

TC390 Series Fixed, TC9938, TC9948A, TC1848B², TC9958², TC9970A, TC1840D2²

TC350 Series Fixed, TC9948A, TC1848B², TC9970A, TC1870P, TC1840D2²

 TC370 Series
 Fixed, TC9938, TC9948A, TC1848B², TC9958², TC9970A, TC1840D2²

 TC551, TC554X
 Fixed, TC9938, TC9948A, TC1848B², TC9958², TC9970A, TC1840D2²

 TC552, TC552X
 Fixed, TC9938, TC9948A, TC1848B², TC9958², TC9970A, TC1840D2²

 TC590 Series
 Fixed, TC9938, TC9948A, TC1848B², TC9958², TC9970A, TC1840D2²

TC651, TC652T, TC654X Fixed, TC9948A, TC1848B², TC9970A, TC1870P, TC1840D2² TC652, TC652X, TC655, TC655X Fixed, TC9948A, TC1848B², TC9970A, TC1870P, TC1840D2²

TC952 Series Fixed
TC972 Series Fixed

1. Applies to all versions within this model number.

2. Also applies to models with pre-position option denoted by a suffix "P".

