


**BOSCH**

Invented for life

# UHI-ASBG-0 Series Indoor Housing



- ▶ For 1/4 in., 1/3 in., and 1/2 in. CCD cameras
- ▶ Feed-through wiring option
- ▶ Glass fiber reinforced ABS
- ▶ Easy installation
- ▶ Full camera accessibility
- ▶ Cost competitive
- ▶ Includes aluminum bracket

The UHI-ASBG-0 Housing is smartly styled for indoor use. This housing meets customers' demands for attractive housings that are both cost competitive and easy to install. They fit a wide range of 1/4 in., 1/3 in., and 1/2 in. format CCD cameras and varifocal lenses.

## Functions

The design of these housings is unique. Removal of two tamper-resistant screws is all that is necessary to open the cover and totally expose the camera and lens. This allows access to all camera and lens controls when the camera is in its mounted position. Power and video cabling can be routed through liquid tight fittings in the bottom or rear of the housing. To complete this set, a sturdy aluminum feed-through mount is added.

## Certifications and Approvals

Product Safety UHI-ASBG-0: CE (APR only)

## Parts Included

Quantity	Component
1	Indoor housing
1	Aluminum bracket

## Technical Specifications

### Electrical

Maximum Camera Power	Max. 10 W 24 VAC–230 VAC, 50/60 Hz, 0.5 A
----------------------	--

### Mechanical

Max Camera/Lens Size (W x H x L)	80 x 60 x 210 mm (3.1 x 2.3 x 8.2 in.)
Cable Entry	Two liquid tight rear fittings accept cable diameters from 6.5 mm to 10.5 mm (0.26 in. to 0.42 in.). Two bottom feed-through liquid tight fittings accept cable diameters from 4.0 mm to 7.0 mm (0.16 in. to 0.28 in.).
Window	3 mm (0.12 in.) thick glass.
Housing Mounting	Includes one J-mount. Four (4) available 1/4 -20 tapped holes.
Camera Mounting	Removable camera bracket. Mounted with one screw.
Construction/Finish	Reinforced with glass fiber ABS, stainless steel hardware.

Finish	Dark mushroom.
Dimensions	See UHI-ASBG-0 drawing.
Weight	1.0 kg (2.2 lb) including Bracket.

### Environmental

Temperature	-10°C (14°F) to 50°C (122°F)
Enclosure Protection	IP30 (indoor use only)

### Ordering Information

<b>UHI-ASBG-0 Series Indoor Housing</b>	<b>UHI-ASBG-0</b>
For camera/lens lengths up to 210 mm (8.2 in.) for APR only	

### Accessories

<b>HAC-TAMP01 Tamper Switch</b>	<b>HAC-TAMP01</b>
Tamper switch kit for HSG and UHI/UHO series enclosures	

**Americas:**  
Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: +31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6258 5511  
Fax: +65 6571 2698  
apr.securitysystems@bosch.com  
www.boschsecurity.com

### Represented by