

Compact Day/Night Camera VBC-265 Series

www.boschsecurity.com



BOSCH
Invented for life



Advantage Line

The VBC-265 Day/Night Camera is a professional surveillance day/night camera that incorporates 10-bit digital signal processing. The camera parameters can be set individually and a Lens Wizard ensures accurate back focusing at all times. The camera has enhanced night viewing compared to normal color cameras. The IR filter switches to monochrome automatically. A through-the-lens IR detector enhances the monochrome mode stability. The automatic black level enhances contrast by compensating for reduced contrast (glare, fog, mist, etc.).

Features

- ▶ Superior picture quality
- ▶ Outstanding resolution (540 TVL)
- ▶ IR sensitivity at night
- ▶ Auto detection of lens
- ▶ Easy to install

2 | Compact Day/Night Camera VBC-265 Series

Technical Specifications

Electrical			
Model No.	Rated Voltage	Range	
VBC-265-11 (C)	12 VDC	10.8-39 VDC	
	24 VAC 50 Hz	12-28 VAC 45-65 Hz	
VBC-265-51 (C)	230 VAC 50 Hz	85-265 VAC 45-65 Hz	
Rated Voltage	12 VDC		
(VBC-265-11, VBC-265-11C)	24 VAC, 50 Hz		
Rated Voltage	230 VAC, 50 Hz		
(VBC-265-51, VBC-265-51C)			
Power Consumption	4 W		
CCD Type	1/3-inch interline		
Active Pixels	752 x 582		
Horizontal Resolution	540 TVL		
Day/Night	Color, Mono, Auto		
Dynamic range	60 db (10-bit image processing)		
Signal-to-Noise Ratio	> 50 dB		
BLC	On (center window weighted), Off		
Gain	20 dB max.		
White Balance	ATW (2500 - 10000 K), AWB hold, Manual WB selectable		
Shutter	Auto (1/50 to 1/150000), fixed, flickerless		
Auto Black	Automatic, Continuous, Off		
Synchronization	Internal, Line Lock selectable		
Lens Mount	CS (maximum lens protrusion 5 mm, 0.2 in), C-mount compatible with adapter ring		
Lens Types	Manual, DC iris and Video iris auto-detect with override DC-iris drive: max. 50 mA continuous Video-iris: 11.5 ± 0.5 VDC, max 50 mA continuous		
Remote Control	Bilinx coaxial communication		
Camera ID	16 character editable string, position selectable		
Alarm Input (TTL)	+5 V nominal, +40 VDC max		
Alarm Output	Monochrome		
Alarm Output Relay	Max. 30 VAC or +40 VDC, Max 0,5 A continuous, 10 VA		
Video Output	1 Vpp, 75 Ohm		
Sensitivity			
(3200 K, scene reflectivity 89%, F1.2)			
	Full video (100 IRE)	Usable picture (50 IRE)	Usable picture (30 IRE)
Color	2.6 lx (0.26 fc)	0.65 lx (0.065 fc)	0.30 lx (0.03 fc)
Mono	1.04 lx (0.104 fc)	0.26 lx (0.026 fc)	0.012 lx (0.0012 fc)

Mechanical	
Dimensions (H x W x L)	58 x 66 x 122 mm (2.28 x 2.6 x 4.8 in) without lens
Weight	450 g (0.99 lbs) without lens
Color	RAL 7035 Light Grey
Tripod Mount	Bottom (isolated) and top 1/4-inch 20 UNC
Environmental	
Operating Temperature	-20°C to +50°C (-4°F to 122°F)
Storage Temperature	-40°C to +70°C (-40°F to +158°F)
Operating Humidity	20% to 93% RH
Storage Humidity	up to 98% RH
Power	
Power connector (VBC-265-11, VBC-265-11C)	Push type connectors, polarity independent, isolated from video output terminals
Power connector (VBC-265-51)	2-wire power cord with Euro plug
Power connector (VBC-265-51C)	2-wire power cord with Chinese plug



Notice

Lens is not included

Certifications and Approvals	
Region	Certification
Europe	CE
Standards	
	FCC Part 15, Class B
	EN55022: Class B
	EN50130-4 Alarm Systems, Part 4
	EN60065
	IEC60068-2-27: Vibration - camera with 500 g (1.1 lb) lens
Ordering Information	
VBC-265-11 Day/Night Camera, 12 VDC/24 VAC	VBC-265-11
VBC-265-51 Day/Night Camera, 230 VAC	VBC-265-51
VBC-265-11C Day/Night Camera, 12 VDC/24 VAC, China	VBC-265-11C
VBC-265-51C Day/Night Camera, 230 VAC, China	VBC-265-51C

Represented by:

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: +31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:
Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:
Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
al.securitysystems@bosch.com
www.boschsecurity.com