


**BOSCH**

Invented for life

# WZ18 Integrated Day/Night High-res Bullet Camera



- ▶ 550 TVL high resolution 1/3 in SuperHAD CCD
- ▶ Mechanical filter for vivid daytime color
- ▶ 20 m (66 ft) of high performance night vision
- ▶ 3 to 12 mm varifocal auto-iris lens
- ▶ IP66 with external zoom and focus adjustments

The WZ18 brings together 550 TVL high resolution imaging, mechanical filter CCD technology and ruthlessly efficient dealer-friendly design. The camera delivers 20 m (66 ft) of high performance night vision.

The WZ18 incorporates 18 LEDs which are powerful enough to drive infrared to a maximum range of 30 m (100 ft). For the purposes of CCTV surveillance imaging, the resulting infrared illumination delivers high performance night vision images up to a distance of 20 m (65 ft).

The WZ18 uses a 1/3 in CCD image sensor, delivering 550 TVL images. Using a dual window IR-Cut and IR-Pass filter, the WZ18 delivers vivid color during day and exceptional performance to infrared at night. The mechanical filter technology helps eliminate focus shift and infrared bleed for effective 24/7 performance.

The WZ18 incorporates a 3 to 12 mm varifocal, auto-iris lens for versatile optical function. Focus and zoom are controlled externally by hand, requiring no tools for adjustments and making WZ18 a true Plug-and-Play camera.

Designed to IP66 environmental standards, WZ18 operates on either 12 VDC or 24 VAC. Photocell-controlled operation increases energy efficiency and ensures accurate day-night switching for outstanding 24/7 performance. A 360° pan / 90° tilt bracket and sunshield are both included as standard.

## Functions

### Applications

- Commercial
- Schools and colleges
- Industrial sites
- Residential
- Warehouses
- Parking lots
- Retail
- Hotels and nightclubs
- Transportation hubs

## Technical Specifications

### Video

Signal Processing	Digital signal processing (DSP)
CCD Camera	1/3 in SuperHAD CCD with Mechanical Filter technology
Filter	Dual-window mechanical type, IR Pass, IR-Cut
Resolution	High resolution 550 TVL
Effective Pixels (H x V)	PAL: 795 x 596, NTSC: 811 x 508
Night-Time Sensitivity	0 lux (infrared on)
Day-Night Switching	Photocell-controlled, automatic
Electronics Iris	1/50 to 1/100,000 s (PAL), 1/60 to 1/100,000 s (NTSC)

Output Signal	1Vpp composite video, 75 ohm
S/N Ratio	Greater than 48 dB
Gamma	0.45
Lens	Varifocal 3.3 to 12mm, DC auto-iris
Lens Control	Externally adjustable zoom, focus and auto-iris
LEDs	Even-distribution infrared array, photocell-controlled
Wavelength	850 nm
Number of LEDs	18

### Electrical

Voltage	12 to 24 VDC or VAC
Power Draw	4.8 W max (IR lamp on)
Power Supply	Not included

### Mechanical

Construction	Robust aluminum extrusion
Finish	Anodized silver
Sunshield	Included as standard
Bracket	360° pan / 90° tilt bracket included as standard
Weight	0.85 kg (1.9 lb)
Dimensions	Ø 76 x 210 (L) mm, (3.0 x 8.3 in)

### Environmental

Operational Temperature	-30 °C to +55 °C, (-22 °F to +131 °F)
Environmental	Designed to IP66

## Ordering Information

**WZ18NV312-0 IDN High-res Bullet Camera**      **WZ18NV312-0**  
 IDN bullet cam, 550TVL, SuperHAD, color switching to bw, mech filter, 18LEDs, silver, NTSC, 3 to 12 mm lens, PSU separate

**WZ18PV312-0 IDN High-res Bullet Camera**      **WZ18PV312-0**  
 IDN bullet cam, 550TVL, SuperHAD, color switching to bw, mech filter, 18LEDs, silver, PAL, 3 to 12 mm lens, PSU separate

### Accessories

**EXPS.008 VAC Power Supply**      **EXPS.008**  
 Power supply 120 VAC / 24 VAC 1500 mA

**WZMB.001 Gang Box Adapter Plate**      **WZMB.001**  
 Gang box adapter plate for WZ18 and WZ20

**PSU-230-24 Power Supply**      **PSU230-24**  
 Power Supply, 230 VAC / 24 VAC, 50 W

**Americas:**  
 Bosch Security Systems, Inc.  
 130 Perinton Parkway  
 Fairport, New York, 14450, USA  
 Phone: +1 800 289 0096  
 Fax: +1 585 223 9180  
 security.sales@us.bosch.com  
 www.boschsecurity.us

**Europe, Middle East, Africa:**  
 Bosch Security Systems B.V.  
 P.O. Box 80002  
 5600 JB Eindhoven, The Netherlands  
 Phone: +31 40 2577 284  
 Fax: +31 40 2577 330  
 emea.securitysystems@bosch.com  
 www.boschsecurity.com

**Asia-Pacific:**  
 Robert Bosch (SEA) Pte Ltd, Security Systems  
 38C Jalan Pemimpin  
 Singapore 577180  
 Phone: +65 6319 3453  
 Fax: +65 6319 3499  
 apr.securitysystems@bosch.com  
 www.boschsecurity.com

### Represented by