

Solenoid Bolts

- * High Security
- * Fail Safe & Fail Secure
- * 12 or 24VDC
- * Stainless Steel
- * Retry Circuit
- * Relay Output (2 in DX series)
- * Indicator Output (DX series)
- * Euro cylinder provision (DX series)
- * Handle override (DX series)



DX-2000 Series



SB-262 (fail safe)

SB-210TS (fail secure)

Specification

Voltage:	12/24vdc
Current:	SB262 - Pull In 1.8A, Run 200mA SB210TS - Pull In 1.8A, Run 200mA DX2000 - Pull In 2.8A, Run 400 mA
Dimensions:	SB262 - 262 x 35 x 35 (l x w x d) SB210TS - 210 x 30 x 35 (l x w x d) DX2000 - 360 x 25 x 47 (l x w x d)

Product Code

SB-262
SB210TS
DX-2025-F
DX-2025-IF
DX-2030-F
DX-2030-IF
DX-2035-F
DX-2035-IF

Solenoid Bolt, Fail Safe
Solenoid Bolt, Fail Secure
Solenoid Bolt, Fail Secure, 25mm Backset
Solenoid Bolt, Fail Safe, 25mm Backset
Solenoid Bolt, Fail Secure, 30mm Backset
Solenoid Bolt, Fail Safe, 30mm Backset
Solenoid Bolt, Fail Secure, 35mm Backset
Solenoid Bolt, Fail Safe, 35mm Backset

*Making your security
a permanent asset...*