

# Convision V740

# Convision V770

<b>Camera Inputs</b>	6 FBAS inputs (PAL, NTSC)
<b>Hard disk</b>	40 or 80 Gbyte
<b>Interfaces</b>	1x RS232 and 1x RS232 or RS485
<b>Module inputs</b>	1x key-operated switch, 6 NC inputs for motion detectors, etc.
<b>Alarm outputs</b>	2x relay outputs, floating
<b>Dome support</b>	e.g. Sensormatic SpeedDome Ultra, Philips G3 AutoDome, Ernitec BDR510, Ernitec BDR550, ECV Telematria, Dennard 2050
<b>ISDN</b>	Euro ISDN, 64 Kbits/s, channel bundling 128 Kbit/s RJ45 Connectors, PPP Protokoll
<b>Ethernet</b>	10/100MBit/s 10 BaseT, RJ45 connector Ethernet
<b>Recording capacity</b>	3-4 fps from each camera when 6 cameras connected
<b>Image format</b>	JPEG, up to 25 fps (PAL), JPEG, up to 30 fps (NTSC)
<b>Image size</b>	192x144, 384x288, 768x288 (with pixel zoom 768x576) Pixel
<b>Compression</b>	approx. 3-50 Kbyte per image, dependent on size and quality
<b>Pre- / post alarm images</b>	32 images with 192x144 or 16 images with 384x288 pixel resolution
<b>Protocol</b>	TCP/IP, PPP, HTTP Server, FTP Server, FTP Client, SMTP Client
<b>Internet browsers</b>	e.g. Netscape Navigator version 4.x upwards, Microsoft Internet Explorer version 4.x upwards
<b>Internet browser features</b>	HTML 3.2, HTTP 1.0, Java Sript 1.2, Java 1.3
<b>Configuration / operation</b>	completely via web browser with HTML
<b>Power consumption</b>	external 12V, 4.0 A multi-norm power supply 100-240 V (GS, CE, UL, CSA)
<b>Dimensions, weight</b>	width: 440 mm, height: 88 mm, depth: 250 mm
<b>Temperature range</b>	0 - 40 °C
<b>Certification</b>	EN50081, EN50082, EN55022

## Product Variations

Convision V740

Convision V770

## Recording Capacities

Per camera using 1 second pulse

Image Size	8KB	16KB	32KB
Convision V740	1456h	728h	364h
Convision V770	2912h	1456h	728h

The Convision V770 sets completely new standards for digital video surveillance, permitting recording at a rate of 3-4 fps from up to 6 connected cameras.

Another new feature is the integrated switchable video output.

With a recording capacity of 2912 hours, the Convision V770 is the prominent digital video recording solution for the security business.



[www.convision.de](http://www.convision.de)

Convision Technology GmbH  
Zuckerbergweg 22  
D 38124 Braunschweig  
Germany  
Tel.: +49-531-2 64 50-0  
Fax: +49-531-2 64 50-10  
e-mail: [info@convision.de](mailto:info@convision.de)

Convision España S.L.  
C / Ter, nº 14 - 2º C  
E 07009 Palma de Mallorca  
Spain  
Tel.: +34-971-70 63 45  
Fax: +34-971-47 26 26  
e-mail: [info@convision.es](mailto:info@convision.es)

**distributed by:**



- suitable for Windows, UNIX, Linux and Macintosh
- ultra high video performance
- time and event controlled recording
- unrestricted configuration memory possibilities
- image storage with up to 32 pre and post alarm images
- video output
- digital recorder

# Convision V700 Series

*Multifunctional CCTV Product*



*IP-Videoserver*

*high quality video performance*

*digital video recording*

*connections for up to 6 cameras*

*video output*

*ISDN and LAN adapter integrated*

*operation via internet browser*

*Convision Safe evaluation software*



VIDEO SOLUTIONS

INTERNET

