# **CM230IR High Security Camera**

The CM230IR forms part of a range of cameras from Conway designed to meet the challenges of environments such as custody suites, prison cells, elevators and public spaces where the installation could be susceptible to physical attack or interference. The unique design of the front panel gives exceptional protection for the camera and lens assembly. Additionally the flush-mounted front facia minimises the risk of the unit being used to attach ligatures. This is important in applications where self-harm is a concern.

The CM230IR is manufactured with a high-quality steel frame that is designed to fit in irregular corners. The front panel consists of a machined steel plate with Lexan™ viewing window. The front panel is further strengthened by a sandwich of machined Acetal that is over 20mm thick.

The inclusion of IR LED illumination ensures that the camera can deliver high quality pictures regardless of light conditions and with the option of 940nM, the CM range is also a very discreet observation solution.

Installation and set-up are straightforward with the two-piece design. The installer firstly fits the frame of the camera and completes the cabling. The camera and front panel can then be offered up to the frame and adjusted for focus and angle. Another unique feature of the CM230IR is the amount of camera angle adjustment that can be achieved. This means the camera can be installed in the room without compromising the room coverage required. As the camera is housed in its own spherical enclosure the chances of damaging the unit during installation and configuration are minimal. Once this is done the installation is completed by fitting the front panel using stainless steel security screws.

The option of a microphone fitted in the housing completes a comprehensive security package.

### **Typical Applications**

Custodial Suites ● Elevators ● Psychiatric Wards ● Interview Rooms ● Stairwells ● Immigration Centres ● Medical Observation Rooms ● Workshops ● Barns

Models	
CM230IR	Day/night camera 2.5mm lens
/a	Optional integrated microphone

assembly

High resolution camera

IR illumination

Privacy masking

On-screen display

Vandal resistant

Anti-ligature design front panel

Angled design for maximum room coverage

Unique camera mount for maximum angle adjustment

Lexan<sup>™</sup> screen

Corner mounting (can mount in irregular corners)

Photocell IR switching

Anti-tamper fixings

Manufactured to weatherproof standard BS.EN60529 Level IP65


Audio (optional)







## **Conway Security Products Limited**



Dimensions (mms)		
Α	370	
В	266	
С	81	

### **Special Finishes**

The CM230IR is available in a variety of special paint finishes. It can also be produced with a brushed aluminium or stainless steel front plate to suit environments such as elevators.

Technical Data	CM230IR
Camera	
Sensor	1/3" Hyper Wide Dynamic Colour Camera (Sony Effio WDR)
Sensitivity	0.1 lux @ f1.2 (colour) 0.05 lux @ f1.2 (mono)
IR Cut Filter	Yes
Wide Dynamic	Yes
Lens	2.5mm standard
Horizontal Angle of View	90° (2.5mm lens)
Resolution	680tvl colour 700tvl mono
Mechanical	
Main Construction	Machined steel front panel
Front Plate	Machined steel facia with Acetal inner
Screen	Clear Lexan™
Fixings	Anti-tamper, stainless steel
Environmental Standard	IP65
Operational Range	-10°C - +50°C
Weight	3.2kg
Finish	Ral9010 powder coat smooth
Power Consumption	3 watts

### **Related Products**

High Security Cameras CM230IR-EXT CM230, CM180DN

Internal Vandal Resistant Housings IHC4, IHW4, IHW4/ck

External Vandal Resistant Housings EHC4, EHW4, EHW4/ck, VEH4



Conway Security Products Limited
Seymore House, Copyground Lane, High Wycombe,
Buckinghamshire HP12 3HE
Tel +44 1494 461373
Fax +44 1494 531685
sales@conway-cctv.co.uk
www.conway-cctv.co.uk

Datasheet D51-4 February 2012

Due to a policy of continual improvement, specifications may be subject to change. Drawings not shown to scale.