

## C.S.P - 300 SERIES INTERNAL WEDGE VANDAL RESISTANT CAMERA



### FEATURES

- High grade mild steel housing
- Polycarbonate window
- Tamper proof screws as standard
- Internal ceiling mounted
- Manual pan and tilt camera cradle
- Vari-focal auto iris lens (option)
- Discrete small housing

Model	300 SM	300 HM	300 H MV	300 SC	300 HC	300 HCV
Mono	1/3" Sony CCD	1/3" Sony CCD	1/3" Sony CCD			
Colour				1/4" Sony CCD	1/3" Sony EX CCD	1/3" Sony Super HAD
Power	12V DC 100mA	12V DC 100mA	12V DC 100mA	12V DC 85mA	12V DC 90mA	12V DC 90mA
Resolution	420TVL	600 TVL	600TVL	380-470 Enhanced	470-580 Enhanced	480 TVL
Sensitivity	0.05 LUX F 2.0	0.05 LUX F 2.0	0.05 LUX F 2.0	0.5 LUX F 1.2	0.3 LUX F 1.2	0.5 LUX F 1.2
Lens	3.6 mm 98°	3.6 mm 98°	Vari-focal auto iris lens 4-9 mm	3.6 mm 68°	3.6 mm 98°	Vari-focal auto Iris lens 4-8 mm
Dimensions:	W 80 x H 80 x D 138 mm (Colour Ivory) Tamper proof screw drive kit (TPD)					

Models 300-SC, 300-HC, Has Mirror image function , Gain Control, Digital Zoom x 2, BLC switchable,

Easy to install cable PCB Board and 1.8 metre BNC / Power Cable on all models.

Ideal for Shops, Schools and Commercial Properties.

Lens options: 2.45, 3.2, 4.0, 6.0, 8.0, 12 mm

Sony Ex-View High 570TVL Mono is now available 0.003 Lux.

