

OUTDOOR ENCLOSURE

The outdoor enclosures provide a cost-effective solution for protecting your D-Link Network Camera from the rigors of outdoor use. The fixed-type enclosures include heavy-duty, angle-adjustable mounting brackets that can be used to secure the camera on a vertical or horizontal surface. These enclosures maximize the full potential of your D-Link Network cameras to secure and protect your home and business.

- *Weatherproof/Dustproof Protection*
- *Heater/Blower for Protection Against Hot/Cold Temperatures*
- *Built-in Power Supply for Easy Cable Management*
- *Angle-Adjustable Mounting Brackets*
- *Vertical or Horizontal Installation*

DCS-45 (IP66 CERTIFIED)

The DCS-45 is IP66 certified for weatherproof and dustproof operation. The housing is complete with an adjustable semi-cable managed bracket.



SUPPORTED DEVICES

- *DCS-3410*
- *DCS-3411*
- *DCS-3110*
- *DCS-3710*

DIMENSIONS (L x W x H)

- *390 x 127 x 124 mm*
(15.4 x 5 x 4.9 inches)

WEIGHT

- *3.0 kg (6.61 lb)*

MATERIAL

- *Aluminum Housing*

COLOR

- *White*

DCS-50 (IP66 CERTIFIED WITH BUILT-IN POWER SUPPLY)

The DCS-50 is IP66 certified for weatherproof and dustproof operation. This model includes a built-in power supply for easy cable management.



SUPPORTED DEVICES

- *DCS-3410*
- *DCS-3411*
- *DCS-3110*
- *DCS-3710*

POWER SUPPLY

- *90 to 264 V AC Input,*
12 V DC, 3 A Output

DIMENSIONS (L x W x H)

- *390 x 127 x 124 mm*
(15.4 x 5 x 4.9 inches)

WEIGHT

- *3.05 kg (6.72 lb)*

MATERIAL

- *Aluminum Housing*

COLOR

- *White*

OPERATING TEMPERATURE

- *-20° to 45° C (-4° to 113° F)*

HUMIDITY

- *5% to 95% RH non-condensing*

DCS-60 (IP44 CERTIFIED WITH BUILT-IN POWER SUPPLY, HEATER AND BLOWER)

The DCS-60 is IP44 certified for weatherproof and dustproof operation. This model includes a heater and blower for a wider range of temperature-sensitive environments. The built-in power supply simplifies the installation procedure.



SUPPORTED DEVICES

- DCS-3410
- DCS-3411
- DCS-3110
- DCS-3710

POWER SUPPLY

- 90 to 264 V AC Input,
12 V DC, 3 A Output

HEATER

- On at 18°C (64°F), Off at 28°C (82°F)

BLOWER

- On at 35°C (95°F), Off at 25°C (77°F)

WEIGHT

- 4.3 kg (9.47 lb)

DIMENSIONS (L x W x H)

- 450 x 135 x 140 mm
(17.7 x 5.3 x 5.5 inches)

MATERIAL

- Aluminum Housing

COLOR

- White

OPERATING TEMPERATURE

- -20° to 45°C (-4° to 113°F)

HUMIDITY

- 0% to 95% RH non-condensing

DCS-70 (DOME TYPE, IP66 CERTIFIED WITH BUILT-IN POWER SUPPLY, HEATER AND BLOWER)

The DCS-70 is a dome-type enclosure designed for use with D-Link's motorized pan and tilt cameras. This IP66 certified enclosure protects your camera against dust and heavy jets of water. Camera installation is simplified with the built-in power supply, while the heater and blower keeps your camera at proper operating temperatures.



SUPPORTED DEVICES

- DCS-5300
- DCS-5610

POWER SUPPLY

- 100 to 240 V AC Input,
12 V DC, 3A Output

HEATER

- On at 0°C (32°F), Off at 10°C (50°F)

BLOWER

- On at 40°C (104°F), Off at 30°C (86°F)

WEIGHT

- 3.4 kg (7.27 lb)

DIMENSIONS (L x W x H)

- 225 x 218 mm
(8.86 x 8.58 inches)

MATERIAL

- Aluminum Housing with Smoked
Acrylic Cover

COLOR

- Beige

OPERATING TEMPERATURE

- -20° to 50°C (-4° to 122°F)

HUMIDITY

- 0% to 95% RH non-condensing

D-Link Corporation
No. 289 Xinhua 3rd Road, Neihu, Taipei 114, Taiwan
Specifications are subject to change without notice.
D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries.
All other trademarks belong to their respective owners.
©2010 D-Link Corporation. All rights reserved.
Release 05 (June 2010)