

At a glance

- 1/3.2" 2 megapixel progressive CMOS sensor
- Fixed fisheye lens for full area surveillance
- Built-in microphone and speaker for 2-way communication
- Micro SD/SDHC Card slot for onboard storage
- High resolution (1600 x 1200)
- ePTZ viewing
- Supports multiple access lists
- Built-in Samba client for saving to a NAS
- 2-Way Audio
- D-ViewCam™ software allows to manage up to 32 network cameras
- mydlink-enabled Cloud Access - Easy remote viewing and management of your camera on your mobile device or through the mydlink website



Key Benefit

The 360° Fisheye cloud enabled network camera, DCS-6010L is equipped with a fisheye lens that enables 180° panoramic view when mounted on a wall or 360° surround view when mounted from a ceiling without blind spots

DCS-6010L

360° Fisheye Cloud Camera

Overview

The DCS-6010L is the first fisheye fixed dome camera from D-link. Built with a fisheye lens and a 2 megapixel sensor makes it perfect for monitoring large areas. You can also access and configure the camera remotely. It comes with a wealth of features that enhance its surveillance capabilities, making it ideal for any situation.

Who is likely to buy it?

Businesses that:

- Need an surveillance system for monitoring larger areas with a single camera.
- Want a simple out-of-the-box remote monitoring and recording solution

Why would they buy it?

- Various display layouts, including original surround view, panoramic views, and regional views for various mounting applications.
- The hemispherical images captured from the fisheye camera can be converted into conventional rectilinear projection for viewing and analysis with the help of latest cutting-edge image processing.
- Ultra-smooth ePTZ function to easily zoom in and focus on a region of interest in both the panoramic and regional viewing modes.
- D-ViewCam™ software simplifies the management process by allowing users to upload a floor plan to create a realistic layout of the premises where cameras are located.

Versus the competition

This camera adopts 2 mega-pixel progressive scan CMOS sensor video stream that covers a larger scene and better quality than any analog CCTV camera. It provides with a high resolution image, an important consideration in video surveillance applications.

The D-ViewCam™ software allows users to manage up to 32 network cameras, set e-mail alert notifications, create recording schedules, and use motion detection to record directly to a hard drive.

New Product Alert

Features

System Requirements	<ul style="list-style-type: none">• Operating System: Microsoft Windows 7/Vista/XP• Internet Explorer 7 or higher , Firefox, or Chrome
Resolution/ Frame Rate	<ul style="list-style-type: none">• 1600 x 1200• 1200 x 900• 800 x 600• 400 x 300
Network Interfaces	<ul style="list-style-type: none">• 10/100BASE-TX Fast Ethernet• 802.11n wireless
Video Codecs	<ul style="list-style-type: none">• H.264• MPEG4• MJPEG
Lens	<ul style="list-style-type: none">• 1/3.2" 2 megapixel progressive CMOS sensor• Focal length: 1.25 mm, F2.0
Digital Zoom	<ul style="list-style-type: none">• Upto 10x
Power	<ul style="list-style-type: none">• Input: 100 to 240 V AC, 50/60 Hz• Output: 5 V DC, 1.2 A
Physical	<ul style="list-style-type: none">• Weight: 267 g \pm 5%
Temperature	<ul style="list-style-type: none">• Operating: 0 to 40 °C (32 to 104 °F)• Storage: -20 to 70 °C (-4 to 158 °F)
Humidity	<ul style="list-style-type: none">• Operating: 20% to 80% non-condensing• Storage: 5% to 95% non-condensing
Certifications	<ul style="list-style-type: none">• CE• CE LVD• FCC• C-Tick



For more information: www.dlink.eu

D-Link European Headquarters. D-Link (Europe) Ltd., D-LinkHouse, Abbey Road, Park Royal, London, NW10 7BX.
Specifications are subject to change without notice. D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries.
All other trademarks belong to their respective owners. ©2012 D-Link Corporation. All rights reserved. E&OE.

Updated 28/05/2012

D-Link®
Building Networks for People