

DH-DVR3224/3232L

24/32 Channel CIF 1.5U Standalone DVR



Features

- > Up to 24/32 cameras with 1080p realtime preview
- > H.264 dual-stream video compression
- > Full channel CIF realtime recording
- > HDMI / VGA / TV / Spot simultaneous video output
- > All channel simultaneous realtime playback, GRID interface & smart search
- > 3D intelligent positioning with Dahua PTZ dome camera
- > Support 2 SATA HDDs up to 8TB, 2 USB2.0
- > Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS

DH-DVR3224/3232L


Technical Specifications

Model	DH-DVR3224L	DH-DVR3232L
System		
Main Processor	Embedded processor	
Operating System	Embedded LINUX	
Video		
Input	24 channel, BNC	32 channel, BNC
Standard	NTSC(525Line, 60f/s), PAL(625Line, 50f/s)	
Audio		
Input	4 channel, BNC	
Output	1 channel, BNC	
Two-way Talk	1 channel Input 1 channel Output(Reuse the audio output channel), BNC	
Display		
Interface	1 HDMI, 1 VGA, 1 TV, 1 Spot, BNC	
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768	
Display Split	1/4/8/9/16/25	1/4/8/9/16/25/36
Privacy Masking	4 rectangular zones (each camera)	
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording	
Recording		
Video/Audio Compression	H.264 / G.711	
Resolution	CIF(352×288/352×240) / QCIF(176×144/176×120)	
Record Rate	Main Stream:	CIF(1~25/30fps)
	Extra Stream	QCIF(1~25/30fps) CIF(1~6/7fps)
Bit Rate	48~2048Kb/s	
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop	
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec	
Video Detection & Alarm		
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen tips	
Video Detection	Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank	
Alarm Input	16 channel	
Relay Output	3 channel	
Playback & Backup		
Sync Playback	1/4/9/16	1/4/9/16
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search	

DH-DVR3224/3232L

Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device / Network / Internal SATA burner
Network	
Ethernet	RJ-45 port (10/100M)
Network Functions	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, Alarm Server
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Storage	
Internal HDD	2 SATA ports (2HDDs or 1HDDs+1CD/DVD-RW), up to 8TB
Auxiliary Interface	
USB Interface	2 ports (1 Rear), USB2.0
RS232	1 port, For PC communication & Keyboard
RS485	1 port, For PTZ control
General	
Power Supply	DC12V/ 3.3A
Power Consumption	25W(without HDD)
Working Environment	-10 ~ +55°C / 10~90%RH / 86~106kpa
Dimension(W×D×H)	1.5U, 325mm×240mm×45mm
Weight	5.0KG(without HDD)

System Connection



Here takes 3232L as an example

DH-DVR3224/3232L

Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email: overseas@dahuatech.com

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2012 Dahua Technology Co., Ltd.