

DH-DVR7804/7808/7816S-U

8/16/32CH Effio 960H & IP 2U Hybrid DVR



Features

- > Up to 8/16/32 channel with 1080p realtime live view
- > H.264/MJPEG decoding & H.264 dual-stream encoding
- > IP: Max 160Mbps incoming bandwidth
- > Analog: 16 channel@960H(960×576/960×480) realtime recording
- > HDMI / VGA / TV/ Spot simultaneous video output
- > All channel synchronous realtime playback, GRID interface & smart search
- > Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videosec, Vivotech , and etc.
- > ONVIF Version 2.0 conformance
- > Auto IP address acquisition by IP Search function
- > 3D intelligent positioning with Dahua PTZ dome camera
- > Support 8 SATA HDDs up to 32TB, 1 eSATA up to 16TB, 4 USB2.0
- > Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS

DH-DVR7804/7808/7816S-U

Technical Specifications


Model	DH-DVR7804S-U	DH-DVR7808S-U	DH-DVR7816S-U
System			
Main Processor	Dual-core embedded processor		
Operating System	Embedded LINUX		
Video			
IP Video Input	4 channel	8 channel	16 channel
Analog Input	4 channel, BNC	8 channel, BNC	16 channel, BNC
Analog Video Standard	NTSC(525Line, 60f/s), PAL(625Line, 50f/s) , Effio 960H camera		
Loop Output	4 channel, BNC	8 channel, BNC	16 channel, BNC
Audio			
Input	4 channel, BNC	8 channel, BNC	16 channel, BNC
Output	1 channel, BNC		
Two-way Talk	1 channel Input, 1 channel Output, BNC		
Display			
Interface	2 HDMI, 1 VGA, 1 TV, 1 Spot, BNC		
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768		
Display Split	1/4/8	1/4/8/9/16	1/4/8/9/16/25/36
Privacy Masking	4 rectangular zones (each camera)		
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording		
Recording			
Video/Audio Compression	H.264 / MJPEG(IP) / G.711		
Resolution	1080P(1920×1080) / 720P(1280×720) / 960H(960×576/960×480) / D1/4CIF(704×576/704×480) / HD1(352×576/352×480) / 2CIF(704×288/704×240) / CIF(352×288/352×240) / QCIF(176×144/176×120)		
Record Rate	IP	Max 160Mbps	
	Analog	All channel@960H (25/30fps)	
Bit Rate	IP: 48~8192 Kb/s, Analog: 48~4096Kb/s		
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop		
Record Interval	1~120 min. (default: 60 min.), Pre-record: 1~30 sec., Post-record: 10~300 sec.		
Video Detection & Alarm			
Trigger Event	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen tips		
Video Detection	Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank		
Alarm Input	4 channel	8 channel	16 channel
Relay Output	6 channel		
Playback & Backup			

DH-DVR7804/7808/7816S-U

Sync Playback	1/4	1/4/9	1/4/9/16
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search		
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom		
Backup Mode	USB Device / eSATA Device / Internal SATA burner/ Network		
Network			
Ethernet	2 RJ-45 port (10/100M/1000M)		
Network Functions	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, Alarm Server, IP Search(Support Dahua IP camera, DVR, NVS and etc.)		
Max. User Access	128 users		
Smart Phone	iPhone, iPad, Android, Windows Phone		
Storage			
Internal HDD	8 SATA ports (8HDDs or 6HDDs+1CD/DVD-RW), up to 32TB		
External HDD	1 eSATA port (Max 4 SATA HDDs), up to 16TB		
Auxiliary Interface			
USB Interface	4 ports (2 Rear), USB2.0		
RS232	1 port, For PC communication & Keyboard		
RS485	1 port, For PTZ control		
General			
Power Supply	AC 100~240 V, 50/60 Hz		
Power Consumption	40W		
Working Environment	-10 ~ +55°C / 10~90%RH / 86~106kpa		
Dimension (W×D×H)	2U, 440mm×460mm×89mm		
Weight	6.5KG(without HDD)		

DH-DVR7804/7808/7816S-U

System Connection



* Take DVR7816S-U as an example

Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email: overseas@dahuatech.com

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2011 Dahua Technology Co., Ltd.