

Accessory

Peripheral

Fixed Bracket

Model	DH-PK0461-X	DH-CA-J20	DH-CA-J30	DH-PK0661-X/DH-PK0561-X
Image				 DH-PK0661-X  DH-WS2770
Material	Al alloy	Al alloy	Al alloy	Al alloy
Installation	Wal	Wall	Wall	Wall
Tilt/Pan	Manual	Manual	N/A	Manual
Weight	0.6Kg	0.3Kg	1Kg	2.5Kg(WS2770), 1.1Kg(PK0661-X)
Load Weight	15Kg	6Kg	15Kg	55Kg(WS2770), 20Kg(PK0661-X)
Dimensions	308×98×82mm	190×80×58mm	250×160×102mm	437×166×142mm(WS2770) 120×103×85mm(PK0661-X)
Applicable Model	Camera F/FW series, Housing DH-PC0462-X	Camera F/FW series	Camera DB/DBW series	Housing DH-PC0462-X/DH-PC0562-X

Housing

Model	DH-PC1461-X	DH-PC0462-X	DH-PC0562-X
Image			
Power Supply	N/A	24VAC±10% / 220VAC±10%	24VAC±10% / 220VAC±10%
Power Consumption	N/A	Heater:25W; Blower:3W	Heater:25W; Blower:3W
Heater	N/A	ON: 8℃±5℃, OFF: 20℃±5℃	ON: 8℃±5℃, OFF: 20℃±5℃
Blower	N/A	ON: 37℃±5℃, OFF: 20℃±5℃	ON: 37℃±5℃, OFF: 20℃±5℃
Materials		Body: Al alloy, Window: Glass or Optical glass optional	Body: Al alloy, Window: Glass or Optical glass optional
Weight	1.0Kg	1.9Kg	2.6Kg
Widow Size (W×H)	85mm×64mm	67mm×57mm	67mm×57mm
Operation Temperature	-5℃ ~ +60℃	-5℃ ~ +60℃	-35℃ ~ +65℃
Ingress Protection	IP65	IP66	IP66
Dimensions(L×W×H)	114mm×93mm×326mm	136×104×376mm	137mm×160mm×452mm
Internal Dimensions (L×W×H)	94mm×89mm×200mm	90×73×235mm	90mm×72.5mm×250mm
Optional Accessories	Optical window	Heater, Blower, Sunshield, Optical window, Wiper	Heater, Blower, Sunshield, Optical window, Wiper