

## Ultra HD Network Video Decoder



### Product Features

- H.265/H.264/MPEG-4 video decoding
- 4ch@12Mp/4ch@4K/16ch@1080P/64ch@D1 decoding ability
- 1ch HDMI input, 4ch HDMI/VGA output, HDMI support Ultra HD 4K output
- Support up to 4 video-wall display units, support configuration of 1\*1,2\*1,2\*2
- Local GUI support mouse operation directly

### Technical Specifications

<b>Model</b>	<b>NVD0405DH-4K</b>
<b>System</b>	
Main Processor	Intel x86 processor
Operating System	Embedded LINUX
<b>Performance</b>	
Video Format	MPEG4/H.264/MJPEG/H.265
Audio Format	PCM/G.711
Video Decoding	D1: 64channels, 2Mbps 960H: 64channels, 2.5Mbps 720P: 36channels, 4Mbps 1080P: 16channels, 8Mbps 800W: 4channels, 12Mbps
Decoding Resolution	QCIF/CIF/2CIF/HD1/D1/960H/720P/1080P/3Mp/5Mp/8Mp/12Mp
Video Frame Rate	PAL:1-25fps ,NTSC:1-30fps
Video Output	4ch@VGA, 4ch@HDMI, 4ch@BNC
Video Input	1ch@HDMI
Video output interface	VGA, HDMI1.4, BNC
Audio Output	4ch BNC
Bi-directional Talk	1 channel, BNC in / BNC out (2Vrms, 10K ohms)

# DH-NVD0405DH-4K



Alarm Input	4ch
Alarm Output	4ch relay out (30VDC 1A, 125VAC, 0.5A)
Communication Interface	1 RJ45 network port (10M/100M/1000M); 1 RS232; RS485
<b>Others</b>	
Power Supply	DC12V, 3.3A
Power Consumption	≤20W
Working Temperature	-10°C~+55°C
Working Humidity	10% ~ 95%, 86Kpa ~ 106Kpa
Unit Dimension	440×300×42.1
Weight	3.25Kg

## **Dahua Technology Co., Ltd.**

1187BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email:overseas@dahuatech.com

www.dahuatech.com

\*Design and specifications are subject to change without notice.

© 2013Dahua Technology Co., Ltd.