

# PFO2910

## 16ch HDCVI Optical Transceiver (Lite)



### Features

- > High definition, real-time
- > Support HDCVI video format 720p/25、 720p/30、 720p/50、 720p/60、 1080p/25、 1080p/30
- > UPnP, easy installation
- > Metal plate is used for the structure, fully enclosed dustproof design
- > Industrial wide temperature design

# PFO2910

## Technical Specifications

Model	PFO2910T	PFO2910R
Physical Port	SFP+ (Single-mode fiber)、16*BNC、2*RS485	
Transmission Distance	0-20km	
Input/ Output Wave Length	1310nm / 1550nm	1550nm / 1310nm
Input Auto Cable Balance	1080p: 75-5 coaxial support 300m 720p : 75-5 coaxial support 500m	
Input/Output Impedance	75Ω	
Sampling Bandwidth	10bit	
Power	DC12V	
Power Consumption	<24W	<20W
Application Humidity	10%—90%	
High&Low temperature	- 40℃~70℃	
Weight	3390g	
Dimension(W×D×H)	440mm×300mm×43.65mm	
Installation	Rack-mounted	

---

### Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email:overseas@dahuatech.com

www.dahuatech.com

\*Design and specifications are subject to change without notice.

© 2012 Dahua Technology Co., Ltd.