

DDF3 000APV Picodome®



The DDF3 000APV is a vandal-resistant UWDR Cam_inPIX® colour Picodome®.

- Horizontal resolution: 540 TV lines
- 1/3" DPS* sensor with Cam_inPIX® technology
- Digital Pixel System* chipset
- Pure 17-bit Digital Signal Processing
- High sensitivity for low-light images at F1.4, 50IRE: 1.0 lux
- Progressive image capture
- Progressive With Segmented Frames (PsF) image data transmission
- IR cut lens coating
- Advanced noise reduction
- Enhanced image quality by means of numerous control functions like AWB, AGC, BLC and extended slow shutter
- Mono-focal lens with F1.4/ f=3.6mm
- Configuration via UTC commands
- Compact, vandal-resistant housing with IP66 (surface mount version)
- PPL (push, point and lock, easy alignment)
- DIN EN 50130-4 compliant

Variants	
200.401.17.002	DDF3 000APV-D Picodome® PAL / Day / white / clear bubble / surface mount variant mono-focal lens F1.4/ 3.6mm
200.401.17.003	DDF3 000APV-D Picodome® PAL / Day / white / clear bubble / surface mount variant HiRes mono-focal lens F2.5/ 2.3mm
200.401.17.004	DDF3 000APV-D Picodome® PAL / Day / white / clear bubble / surface mount variant mono-focal lens F1.8/ 6mm
200.401.18.002	DDF3 000APV-D Picodome® PAL / Day / white / clear bubble / in-ceiling mount variant mono-focal lens F1.4/ 3.6mm
200.401.18.003	DDF3 000APV-D Picodome® PAL / Day / white / clear bubble / in-ceiling mount variant HiRes mono-focal lens F2.5/ 2.3mm
200.401.18.004	DDF3 000APV-D Picodome® PAL / Day / white / clear bubble / in-ceiling mount variant mono-focal lens F1.8/ 6mm

Options	
200.401.17.05.03	Mounting ring for surface mount variants, standard adapter ring, lateral cable routing, screw connection at flush-mounted sockets according to DIN 49073 (D=68mm and D=74mm),
200.401.17.05.11	Angular adapter for surface mount variants, 15° adapter ring, angle of view with wall/ceiling mounting of 90°, lateral cable routing, screw connection at flush-mounted sockets according to DIN 49073 (D=68mm and D=74mm),
200.401.17.999	Design colours: Depending on customer demand, housing colour available according to RAL or Pantone colour scale / for surface mount variants., For enquires please contact design@dallmeier.com
200.401.18.999	Design colours: Depending on customer demand, housing colour available according to RAL or Pantone colour scale / for in-ceiling mount variants., For enquires please contact design@dallmeier.com
100.043	Voltage converter 24V AC on 12V DC
200.440	PicoRemote, UTC Remote Box for analogue Cam_inPIX® cameras, More information can be found in our Partner Forum under "Documentations".
100.042	Universal power pack 110-240V AC / 12V DC, removable adapter EU/UK/US/AUS
200.434.1.001	MicroStreamer-PoE, PAL / grey

