

3 GALLIFORD ROAD INDUSTRIAL ESTATE HEYBRIDGE MALDON ESSEX CM9 4XD

TEL: MALDON (01621) 856850 FAX: MALDON (01621) 856162 Email: dantech@dantech.uk.com Website: www.dantech.uk.com

PRODUCT DATA SHEET FOR DA399

PRODUCT DESCRIPTION

A 3 Amp 12V DC (13.7) power supply with 4 individually fused outputs, which will house and charge one VRLA battery up to 7Ah capacity. Unit comes with SPCO contacts for indicating mains fail and low voltage states and also has a tamper microswitch. Steel cased.

PRODUCT SPECIFICATION

General Electrical and Mechanical Specification

•	Supply Voltage:	240V AC 50Hz
•	Current Consumption:	<pre>< 110VA at full load</pre>
•	Colour:	White
•	Size in mm (W x H x D):	210 x 260 x 80
•	Weight in Kg:	3.625
•	Packed Size in mm (W x H x D):	218 x 280 x 83
•	Packed Weight in Kg:	3.800
•	Case Material:	1.2 mm Powder coated Mild Steel
•	Operating Temperature:	10°C to +40°C
•	Storage Temperature:	20°C to +50°C
•	Operating Relative Humidity:	up to 95% non condensing
•	MTBF:	50,000 hours
•	CE approved:	

Other Relevant Specification

•	Output Voltage:	12V DC (nominal 13.7V DC)
•	Current:	3A max total
•	Mains Fail Indication:	Yes
•	Low Volts Indication:	Yes
•	Recommended Battery Size:	7Ah
•	Tamper Switch:	Yes